

-----  
 SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
 -----

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . . : 06094 697649 604  
 PRODUCT NAME . . . . : #912 CORVETTE AMERICA 4321-23 DK SADDLE 73  
 PRODUCT CLASS . . . . : Aerosol Touch-Up

MSDS PREPARATION DATE : 04/01/2010

MANUFACTURER IDENTIFICATION:

RAABE COMPANY (Brydara)  
 PO BOX 1090

CUSTOMER IDENTIFICATION:

CORVETTE AMERICA  
 100 CLASSIC CAR DRIVE

MENOMONEE FALLS

WI 53052-1090

REEDSVILLE

PA 17084

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
 INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
 8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

-----  
 SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS  
 -----

1 ETHYL ACETATE

CAS# 141-78-6

ETHYL ACETATE

PCT BY WT: 17.0000 VAPOR PRESSURE: 76.000 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm  
 ACGIH TLV-STEL NO INFO  
 OSHA PEL-TWA 400 ppm  
 COMPANY N.E.  
 LD50 (ORAL) 4935 mg/kg (Rabbit)  
 LD50 (DERMAL) 17962 mg/kg (Rabbit)  
 LC50 45000 mg/m3 (Mouse)

2 ETHYLBENZENE

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: .3980 VAPOR PRESSURE: 7.000 MMHG @ 68F LEL .80

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm  
 ACGIH TLV-STEL 125 ppm  
 OSHA PEL-TWA 100 ppm  
 OSHA PEL-STEL 125 ppm  
 OTHER IARC (2B), CALIFORNIA PROP 65 (Cancer 6/11/2004)  
 LD50 (ORAL) 3500 mg/kg (rat)  
 LD50 (DERMAL) 20574 mg/kg (rabbit)  
 LC50 17623 mg/m3 (rat)

OTHER LIMITS:

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----  
PROP 65-Cancer, listed 6/11/04 EINECS 202-849-4  
-----

3 1-METHYL-2-PYRROLIDONE  
CAS# 872-50-4  
1-METHYL-2-PYRROLIDONE LEL 2.10  
PCT BY WT: 1.0000  
EXPOSURE LIMIT:  
ACGIH TLV-TWA NO INFO  
ACGIH TLV-STEL NO INFO  
OTHER CALIFORNIA PROP 65-Developmental (listed 6/15/01)  
OTHER LIMITS: EINECS 212-828-1  
-----

4 TITANIUM DIOXIDE  
CAS# 13463-67-7  
TITANIUM DIOXIDE  
PCT BY WT: 3.0000  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 10 mg/m3  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 10 mg/m3  
COMPANY N.E.  
LD50 (ORAL) > 24000 mg/kg (rat)  
LC50 > 6820 mg/m3 (rat)  
OTHER LIMITS: EINECS 236-675-5  
-----

5 VINYL RESIN  
CAS# 9003-22-9  
VINYL RESIN LEL 100.00  
PCT BY WT: 1.0000  
EXPOSURE LIMIT:  
ACGIH TLV-TWA NO INFO  
ACGIH TLV-STEL NO INFO  
-----

6 XYLENE  
CAS# 1330-20-7  
XYLENE VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00  
PCT BY WT: 3.0000  
EXPOSURE LIMIT:  
ACGIH TLV-TWA 100 ppm  
ACGIH TLV-STEL 150 ppm  
OSHA PEL-TWA 100 ppm  
OSHA PEL-STEL 150 ppm  
COMPANY N.E.  
LD50 (ORAL) 4300 mg/kg (rat)  
LD50 (DERMAL) 1700 mg/kg (rabbit)  
LC50 18892 mg/m3 (rat)

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

OTHER LIMITS:

EINECS 215-535-7

7 DIMETHYL ETHER

CAS# 115-10-6

DIMETHYL ETHER

PCT BY WT: 40.0000

LEL 3.40

EXPOSURE LIMIT:

ACGIH TLV-TWA 1000PPM

ACGIH TLV-STEL 1000PPM

8 BUTYL BENZYL PHTHALATE

CAS# 85-68-7

BUTYL BENZYL PHTHALATE

PCT BY WT: 1.0000

LEL .30

EXPOSURE LIMIT:

ACGIH TLV-TWA 5 mg/m3

ACGIH TLV-STEL N.E.

OSHA PEL-TWA 5 mg/m3

OTHER CALIFORNIA PROP 65-Developmental (listed 12/2/05)

OTHER LIMITS:

EINECS 201-622-7

9 METHYL ETHYL KETONE

CAS# 78-93-3

METHYL ETHYL KETONE

PCT BY WT: 23.0000

VAPOR PRESSURE:

85.000 MMHG @ 68F

LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 200 ppm

ACGIH TLV-STEL 300 ppm

OSHA PEL-TWA 200 ppm

COMPANY N.E.

LD50 (ORAL) 2737 mg/kg (rat)

LD50 (DERMAL) 6480 mg/kg (rat)

LC50 23500 mg/m3 (rat)

OTHER LIMITS:

EINECS 201-159-0

\*\*\*\*\*  
This product contains one or more reported carcinogens or suspected  
carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits  
recommended column.  
\*\*\*\*\*  
This substance is classified as a hazardous air pollutant.  
\*\*\*\*\*

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----  
SECTION 3 - HAZARDS IDENTIFICATION  
-----

EMERGENCY OVERVIEW:

Harmful if inhaled.  
Harmful if absorbed through skin.  
Causes eye irritation.  
Causes skin irritation.  
Vapors irritating to eyes and respiratory tract.  
Flammable liquid and vapor.  
Vapors may cause flash fire or explosion.  
Aerosol Product.  
Contents under pressure.

EYE:

May cause eye burns.

SKIN:

May cause skin irritation.  
Prolonged contact with the skin can cause chemical burns.  
Liquid contact with skin may cause frostbite.  
Harmful if absorbed through the skin.  
Skin contact may aggravate an existing dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.  
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.  
Excessive inhalation of vapors can cause nasal and respiratory irritation.  
Breathing high concentrations of vapors may cause anesthetic effects.  
Liquid or vapor may be irritating to skin, eyes, throat or lungs.  
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.  
Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to material(s) in this product.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.  
May cause serious health effects if swallowed.  
Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.  
May cause nausea, vomiting and diarrhea.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

Kidney damage  
Eye damage  
Lung damage  
Liver damage

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

Anemia  
Brain damage

Chronic overexposure to a component or components is this product has been suggested as a cause of the following effects in humans:

Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Contains butyl benzyl phthalate which has been shown to cause cancer in at least one study in laboratory animals. Butyl benzyl phthalate is listed by the National Toxicology Program (NTP) as producing significant maternal and developmental toxicity.

Rats exposed to titanium dioxide dust at 250 mg/m3 developed lung cancer, however, such exposure levels are not attainable in the workplace with this material.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

-----  
SECTION 4 - FIRST AID MEASURES  
-----

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

-----  
SECTION 5 - FIRE FIGHTING MEASURES  
-----

RE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint . . . . . : 24.0 °F

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----  
Explosion Level . . . . . : Low (LEL) - .3  
High (UEL) - 100.0

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back. Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred. Exposure to heat builds up pressure in closed containers. Cool with water spray.

-----  
SECTION 6 - ACCIDENTAL RELEASE MEASURES

-----  
CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire. Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

-----  
SECTION 7 - HANDLING AND STORAGE

-----  
HANDLING:

Wash hands thoroughly after handling. This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as: Warning! This product contains a chemical or chemicals known to the State of California to cause cancer. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2. Keep away from heat, sparks and flame. Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component (see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure . . . . .	:	85.00	mm Hg @ 20 C
Vapor Density . . . . .	:	3.70	
Boiling Range . . . . .	:	Lower -	77.0 °F
	:	Higher -	500.0 °F
Specific Gravity . . . . .	:	.790	
Formula Weight per Volume . . . . .	:		6.5784 LB/GL
VOC (Calculated, LB/GAL) . . . . .	:	5.883	
VOC (Calculated, GM/L) . . . . .	:	704.95	
Percent Volatile by Weight . . . . .	:	89.3621	
Percent Volatile by Volume . . . . .	:	93.7785	
Evaporation Rate . . . . .	:	6.000	(n-Butyl Acetate = 1)
Viscosity . . . . .	:	-N/A	

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:

Strong oxidizing agents.  
Incompatible with air, and dibenzoyl peroxide

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----  
POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.  
-----

SECTION 11 - TOXICOLOGICAL INFORMATION

-----  
No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.  
-----

SECTION 12 - ECOLOGICAL INFORMATION

-----  
No specific ecological information is available for this product.  
-----

SECTION 13 - DISPOSAL CONSIDERATIONS

-----  
WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.  
-----

SECTION 14 - TRANSPORT INFORMATION

-----  
Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)  
-----

SECTION 15 - REGULATORY INFORMATION

-----  
SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

1,4-DIHYLBENZENE

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

CAS#	100-41-4	PCT BY WT:	.3980
1-METHYL-2-PYRROLIDONE			
CAS#	872-50-4	PCT BY WT:	1.0660
XYLENE			
CAS#	1330-20-7	PCT BY WT:	2.5940
MIBK - Methyl Isobutyl Ketone			
		PCT BY WT:	4.8460
***	4-Methyl-2-pentanone		
	CAS# 108-10-1	PCT BY WT:	4.8460

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:  
Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.  
Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

CHEMICAL NAME	CAS NUMBER
---------------	------------

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

CHEMICAL NAME	CAS NUMBER
---------------	------------

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make

RAABE COMPANY  
MATERIAL SAFETY DATA SHEET

06094 697649 604

-----  
no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2\*    FLAMMABILITY: 4    REACTIVITY: 0    PERSONAL PROTECTION: X