



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: KEROSENE ULSK-1 DYED

Manufacturer Information:

Philadelphia Energy Solutions
3144 West Passyunk Ave

Philadelphia, Pennsylvania, 19145
msds@PES-Companies.com

Product Use:

ULTRA LOW SULFUR KEROSENE-K1

Emergency Phone Number (24 Hours): 215-339-5400

Information: (8AM-4PM) 215-339-2000

2. HAZARDS IDENTIFICATION

• **EMERGENCY OVERVIEW**

Danger! Combustible. High vapor concentrations may cause drowsiness. May cause skin irritation. Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage. Contains material or materials that may cause cancer based on animal data.

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>PPI</u>
NFPA	2	2	0	
HMIS	2	2	0	X

• **POTENTIAL HEALTH EFFECTS**

▪ **INHALATION**

High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death). High vapor concentrations are irritating to the eyes, nose, throat, and lungs.

▪ **SKIN**

Practically non-toxic if absorbed through the skin. Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Contains a material that has caused skin tumors in laboratory animals.

▪ **EYES**

Mildly irritating to the eyes. Contact with the eye may cause redness, burning, tearing and/or blurred vision.

- **INGESTION**

Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage.

- **PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, nervous system, respiratory system, lung (asthma-like conditions),

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
HYDRODESULFURIZED KEROSENE	64742-81-0	99 - 100
NAPHTHALENE	91-20-3	0 - 3
XYLENE	1330-20-7	0 - 0.9
TOLUENE	108-88-3	0 - 0.3
ETHYL BENZENE	100-41-4	0 - 0.2
N-HEXANE	110-54-3	0 - 0.1
BENZENE	71-43-2	0 - 0.07
CUMENE	98-82-8	0 - 0.07
PROPRIETARY ADDITIVES		0 - 0.01

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	CAS No.	Governing Body	Exposure Limits		
Limit for the product		ACGIH	TLV	30	ppm
BENZENE	71-43-2	ACGIH	STEL	2.5	ppm
BENZENE	71-43-2	OSHA	STEL	5	ppm
BENZENE	71-43-2	ACGIH	TWA	0.5	ppm
BENZENE	71-43-2	OSHA	TWA	1	ppm
CUMENE	98-82-8	ACGIH	TWA	50	ppm
CUMENE	98-82-8	OSHA	TWA	50	ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA	20	ppm
ETHYL BENZENE	100-41-4	OSHA	TWA	100	ppm
N-HEXANE	110-54-3	ACGIH	TWA	50	ppm
N-HEXANE	110-54-3	OSHA	TWA	500	ppm
NAPHTHALENE	91-20-3	ACGIH	STEL	15	ppm
NAPHTHALENE	91-20-3	ACGIH	TWA	10	ppm
NAPHTHALENE	91-20-3	OSHA	TWA	10	ppm
TOLUENE	108-88-3	NIOSH	STEL	150	ppm
TOLUENE	108-88-3	ACGIH	TWA	20	ppm
TOLUENE	108-88-3	OSHA	TWA	200	ppm
XYLENE	1330-20-7	ACGIH	STEL	150	ppm
XYLENE	1330-20-7	ACGIH	TWA	100	ppm
XYLENE	1330-20-7	OSHA	TWA	100	ppm
HYDRODESULFURIZED KEROSENE	64742-81-0	ACGIH	TWA	200	mg/m3
HYDRODESULFURIZED KEROSENE	64742-81-0	ACGIH	TLV	30	ppm

4. FIRST AID MEASURES

- **INHALATION**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

- **SKIN**

Wash with soap and water for 20 minutes. Get medical attention if irritation develops or persists. Wash clothing before reuse.

- **EYES**
Flush eye with water for 20 minutes. Get medical attention.
- **INGESTION**
Do not induce vomiting! Do not give liquids! Get medical attention immediately.

5. FIRE FIGHTING MEASURES

- **EXTINGUISHING MEDIA**
Regular foam; Dry chemical; Carbon dioxide; Water may be ineffective.
- **FIRE FIGHTING INSTRUCTIONS**
Use water spray to cool fire exposed tanks and containers. Wear structural fire fighting gear. The use of fresh air equipment such as Self Contained Breathing Apparatus (SCBA) or Supplied Air Respirators should be worn for fire fighting if exposure or potential exposure to products of combustion is expected.
- **FLAMMABLE PROPERTIES**
Combustible Liquid. Can form explosive mixtures at temperatures at or above the flashpoint.

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				125 MINIMUM TCC	F	N/A
Autoignition Temperature				410 ESTIMATED	F	N/A
Lower Explosion Limit	0.7				%	N/A
Upper Explosion Limit	5				%	N/A

6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

- **HANDLING**
Follow all MSDS/label precautions even after container is emptied because it may retain product residue. Use only in a well-ventilated area. Ground and bond containers when transferring material. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling. Never siphon by mouth. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioned, or properly disposed of.
- **STORAGE**
Keep away from heat, sparks, and flame. Keep container closed when not in use. Store in a cool place in original container and protect from sunlight. Outside or detached storage is preferred. NFPA class II storage. Flash point is greater than 100 degrees F and less than 140 degrees F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

- **ENGINEERING CONTROLS**
Use with adequate ventilation. Mechanical ventilation recommended. Good general ventilation should be sufficient to control airborne levels.

- **PERSONAL PROTECTION**

- **EYE PROTECTION**

Splash proof chemical goggles are recommended to protect against the splash of product.

- **GLOVES or HAND PROTECTION**

The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polyvinyl chloride (PVC); Neoprene; Nitrile; Polyvinyl alcohol; Viton; Polyethylene;

- **RESPIRATORY PROTECTION**

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

- **OTHER**

Where splashing is possible, full chemically resistant protective clothing and boots are required. The following materials are acceptable for use as protective clothing: Polyvinyl alcohol (PVA); Polyvinyl chloride (PVC); Neoprene; Nitrile; Viton; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	CLEAR OR RED LIQUID	
Boiling Point		F	304 - 574	
Bulk Density		lb/gal	no data	
Liquid Conductivity		pS/m	1 - 50	
Melting Point		F	< -40	
Molecular Weight		g/mole	no data	
Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.81	N/A		
Solubility In Water		wt %	SLight	
Odor		N/A	KEROSENE ODOR.	
Odor Threshold	0.1	ppm		
Vapor Pressure	0.4	mmHg		
Viscosity (F)		SUS	no data	
Viscosity (C)	1.9	CsT		@ 40 C
% Volatile		wt %	98 - 100	

10. STABILITY AND REACTIVITY

- **STABILITY**

Stable

- **CONDITIONS TO AVOID**
Avoid heat, sparks and open flame.
- **INCOMPATIBILITY**
The following materials are incompatible with this product: Strong oxidizers such as chlorine, peroxides, chromates, nitric acid, perchlorates, concentrated oxygen, sodium hypochlorite, calcium hypochlorite and permanganates. Chlorine; Concentrated oxygen; Sodium hypochlorite; Calcium hypochlorite;
- **HAZARDOUS DECOMPOSITION PRODUCTS**
Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.
- **HAZARDOUS POLYMERIZATION**
Will not polymerize.

11. TOXICOLOGY INFORMATION

Single Exposure Health Effects

Oral:

LD50 (g/kg): no data

Dermal:

LD50 (mg/kg): no data

Inhalation:

LC50 (mg/l): no data

LC50 (mg/m³): no data

LC50 (ppm): no data

Component Toxicity Information

Additional Toxicology Information

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

14. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>
DOT	Ground	Kerosene

<u>Governing Body</u>	<u>Mode</u>	<u>Hazard Class</u>	<u>UN/NA No.</u>	<u>Label</u>
DOT	Ground	3 (Flammable liquid)	1223	

15. REGULATORY INFORMATION

Regulatory List	Component	CAS No.
ACGIH - Occupational Exposure Limits - Carcinogens	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - Carcinogens	HYDRODESULFURIZED KEROSENE	64742-81-0
ACGIH - Occupational Exposure Limits - Carcinogens	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - Carcinogens	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - Carcinogens	XYLENE	1330-20-7
ACGIH - Occupational Exposure Limits - TWAs	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - TWAs	CUMENE	98-82-8
ACGIH - Occupational Exposure Limits - TWAs	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - TWAs	HYDRODESULFURIZED KEROSENE	64742-81-0
ACGIH - Occupational Exposure Limits - TWAs	N-HEXANE	110-54-3
ACGIH - Occupational Exposure Limits - TWAs	NAPHTHALENE	91-20-3
ACGIH - Occupational Exposure Limits - TWAs	TOLUENE	108-88-3
ACGIH - Occupational Exposure Limits - TWAs	XYLENE	1330-20-7
ACGIH - Short Term Exposure Limits	BENZENE	71-43-2
ACGIH - Short Term Exposure Limits	ETHYL BENZENE	100-41-4
ACGIH - Short Term Exposure Limits	NAPHTHALENE	91-20-3
ACGIH - Short Term Exposure Limits	XYLENE	1330-20-7
ACGIH - Skin Absorption Designation	BENZENE	71-43-2
ACGIH - Skin Absorption Designation	HYDRODESULFURIZED KEROSENE	64742-81-0
ACGIH - Skin Absorption Designation	N-HEXANE	110-54-3
ACGIH - Skin Absorption Designation	NAPHTHALENE	91-20-3
CAA (Clean Air Act) - High Risk Haz Air Pollutants	BENZENE	71-43-2
CAA (Clean Air Act) - HON Rule - Organic HAPs	BENZENE	71-43-2
CAA (Clean Air Act) - HON Rule - Organic HAPs	CUMENE	98-82-8
CAA (Clean Air Act) - HON Rule - Organic HAPs	ETHYL BENZENE	100-41-4
CAA (Clean Air Act) - HON Rule - Organic HAPs	N-HEXANE	110-54-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	NAPHTHALENE	91-20-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	TOLUENE	108-88-3
CAA (Clean Air Act) - HON Rule - Organic HAPs	XYLENE	1330-20-7
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	BENZENE	71-43-2
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	CUMENE	98-82-8
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	ETHYL BENZENE	100-41-4
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	N-HEXANE	110-54-3
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	NAPHTHALENE	91-20-3
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	TOLUENE	108-88-3
CAA (Clean Air Act) - HON Rule - SOCMi Chemicals	XYLENE	1330-20-7
CAA (Clean Air Act) - VOCs in SOCMi	BENZENE	71-43-2
CAA (Clean Air Act) - VOCs in SOCMi	CUMENE	98-82-8
CAA (Clean Air Act) - VOCs in SOCMi	ETHYL BENZENE	100-41-4
CAA (Clean Air Act) - VOCs in SOCMi	TOLUENE	108-88-3
CAA (Clean Air Act) - VOCs in SOCMi	XYLENE	1330-20-7
CAA - 1990 Hazardous Air Pollutants	BENZENE	71-43-2
CAA - 1990 Hazardous Air Pollutants	CUMENE	98-82-8
CAA - 1990 Hazardous Air Pollutants	ETHYL BENZENE	100-41-4
CAA - 1990 Hazardous Air Pollutants	N-HEXANE	110-54-3
CAA - 1990 Hazardous Air Pollutants	NAPHTHALENE	91-20-3
CAA - 1990 Hazardous Air Pollutants	TOLUENE	108-88-3
CAA - 1990 Hazardous Air Pollutants	XYLENE	1330-20-7
California - Prop. 65 - Developmental Toxicity	BENZENE	71-43-2
California - Prop. 65 - Developmental Toxicity	TOLUENE	108-88-3
California - Prop. 65 - Reproductive - Female	TOLUENE	108-88-3
California - Prop. 65 - Reproductive - Male	BENZENE	71-43-2
California - Proposition 65 - Carcinogens List	BENZENE	71-43-2

California - Proposition 65 - Carcinogens List	ETHYL BENZENE	100-41-4
California - Proposition 65 - Carcinogens List	NAPHTHALENE	91-20-3
Canada - CEPA - Sch. I - List of Toxic Substances	BENZENE	71-43-2
Canada - WHMIS - Ingredient Disclosure	ETHYL BENZENE	100-41-4
Canada - WHMIS - Ingredient Disclosure	N-HEXANE	110-54-3
Canada - WHMIS - Ingredient Disclosure	TOLUENE	108-88-3
CERCLA/SARA - Haz Substances and their RQs	BENZENE	71-43-2
CERCLA/SARA - Haz Substances and their RQs	CUMENE	98-82-8
CERCLA/SARA - Haz Substances and their RQs	ETHYL BENZENE	100-41-4
CERCLA/SARA - Haz Substances and their RQs	N-HEXANE	110-54-3
CERCLA/SARA - Haz Substances and their RQs	NAPHTHALENE	91-20-3
CERCLA/SARA - Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA - Haz Substances and their RQs	XYLENE	1330-20-7
CERCLA/SARA - Section 313 - Emission Reporting	BENZENE	71-43-2
CERCLA/SARA - Section 313 - Emission Reporting	CUMENE	98-82-8
CERCLA/SARA - Section 313 - Emission Reporting	ETHYL BENZENE	100-41-4
CERCLA/SARA - Section 313 - Emission Reporting	N-HEXANE	110-54-3
CERCLA/SARA - Section 313 - Emission Reporting	NAPHTHALENE	91-20-3
CERCLA/SARA - Section 313 - Emission Reporting	TOLUENE	108-88-3
CERCLA/SARA - Section 313 - Emission Reporting	XYLENE	1330-20-7
CWA (Clean Water Act) - Hazardous Substances	BENZENE	71-43-2
CWA (Clean Water Act) - Hazardous Substances	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Hazardous Substances	NAPHTHALENE	91-20-3
CWA (Clean Water Act) - Hazardous Substances	TOLUENE	108-88-3
CWA (Clean Water Act) - Hazardous Substances	XYLENE	1330-20-7
CWA (Clean Water Act) - Priority Pollutants	BENZENE	71-43-2
CWA (Clean Water Act) - Priority Pollutants	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Priority Pollutants	NAPHTHALENE	91-20-3
CWA (Clean Water Act) - Priority Pollutants	TOLUENE	108-88-3
CWA (Clean Water Act) - Priority Pollutants	BENZENE	71-43-2
CWA (Clean Water Act) - Toxic Pollutants	ETHYL BENZENE	100-41-4
CWA (Clean Water Act) - Toxic Pollutants	NAPHTHALENE	91-20-3
CWA (Clean Water Act) - Toxic Pollutants	TOLUENE	108-88-3
DEA - List II Essential Chemicals	TOLUENE	108-88-3
IARC - Group 1 (carcinogenic to humans)	BENZENE	71-43-2
IARC - Group 2B (Possibly carcinogenic to humans)	ETHYL BENZENE	100-41-4
IARC - Group 2B (Possibly carcinogenic to humans)	NAPHTHALENE	91-20-3
IARC - Group 3 (not classifiable)	TOLUENE	108-88-3
IARC - Group 3 (not classifiable)	XYLENE	1330-20-7
Inventory - Australia (AICS)	BENZENE	71-43-2
Inventory - Australia (AICS)	CUMENE	98-82-8
Inventory - Australia (AICS)	ETHYL BENZENE	100-41-4
Inventory - Australia (AICS)	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - Australia (AICS)	N-HEXANE	110-54-3
Inventory - Australia (AICS)	NAPHTHALENE	91-20-3
Inventory - Australia (AICS)	TOLUENE	108-88-3
Inventory - Australia (AICS)	XYLENE	1330-20-7
Inventory - Canada - Domestic Substances List	BENZENE	71-43-2
Inventory - Canada - Domestic Substances List	CUMENE	98-82-8
Inventory - Canada - Domestic Substances List	ETHYL BENZENE	100-41-4
Inventory - Canada - Domestic Substances List	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - Canada - Domestic Substances List	N-HEXANE	110-54-3
Inventory - Canada - Domestic Substances List	NAPHTHALENE	91-20-3
Inventory - Canada - Domestic Substances List	TOLUENE	108-88-3
Inventory - Canada - Domestic Substances List	XYLENE	1330-20-7
Inventory - China	BENZENE	71-43-2
Inventory - China	CUMENE	98-82-8
Inventory - China	ETHYL BENZENE	100-41-4
Inventory - China	HYDRODESULFURIZED	64742-81-0
	KEROSENE	

Inventory - China	N-HEXANE	110-54-3
Inventory - China	NAPHTHALENE	91-20-3
Inventory - China	TOLUENE	108-88-3
Inventory - China	XYLENE	1330-20-7
Inventory - European EINECS Inventory	BENZENE	71-43-2
Inventory - European EINECS Inventory	CUMENE	98-82-8
Inventory - European EINECS Inventory	ETHYL BENZENE	100-41-4
Inventory - European EINECS Inventory	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - European EINECS Inventory	N-HEXANE	110-54-3
Inventory - European EINECS Inventory	NAPHTHALENE	91-20-3
Inventory - European EINECS Inventory	TOLUENE	108-88-3
Inventory - European EINECS Inventory	XYLENE	1330-20-7
Inventory - Japan - (ENCS)	BENZENE	71-43-2
Inventory - Japan - (ENCS)	CUMENE	98-82-8
Inventory - Japan - (ENCS)	ETHYL BENZENE	100-41-4
Inventory - Japan - (ENCS)	N-HEXANE	110-54-3
Inventory - Japan - (ENCS)	NAPHTHALENE	91-20-3
Inventory - Japan - (ENCS)	TOLUENE	108-88-3
Inventory - Japan - (ENCS)	XYLENE	1330-20-7
Inventory - Japan - (ENCS)	BENZENE	71-43-2
Inventory - Korea - Existing and Evaluated	CUMENE	98-82-8
Inventory - Korea - Existing and Evaluated	ETHYL BENZENE	100-41-4
Inventory - Korea - Existing and Evaluated	HYDRODESULFURIZED	64742-81-0
Inventory - Korea - Existing and Evaluated	KEROSENE	
Inventory - Korea - Existing and Evaluated	N-HEXANE	110-54-3
Inventory - Korea - Existing and Evaluated	NAPHTHALENE	91-20-3
Inventory - Korea - Existing and Evaluated	TOLUENE	108-88-3
Inventory - Korea - Existing and Evaluated	XYLENE	1330-20-7
Inventory - New Zealand	BENZENE	71-43-2
Inventory - New Zealand	CUMENE	98-82-8
Inventory - New Zealand	ETHYL BENZENE	100-41-4
Inventory - New Zealand	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - New Zealand	N-HEXANE	110-54-3
Inventory - New Zealand	NAPHTHALENE	91-20-3
Inventory - New Zealand	TOLUENE	108-88-3
Inventory - New Zealand	XYLENE	1330-20-7
Inventory - Philippines Inventory (PICCS)	BENZENE	71-43-2
Inventory - Philippines Inventory (PICCS)	CUMENE	98-82-8
Inventory - Philippines Inventory (PICCS)	ETHYL BENZENE	100-41-4
Inventory - Philippines Inventory (PICCS)	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - Philippines Inventory (PICCS)	N-HEXANE	110-54-3
Inventory - Philippines Inventory (PICCS)	NAPHTHALENE	91-20-3
Inventory - Philippines Inventory (PICCS)	TOLUENE	108-88-3
Inventory - Philippines Inventory (PICCS)	XYLENE	1330-20-7
Inventory - TSCA - Sect. 8(b) Inventory	BENZENE	71-43-2
Inventory - TSCA - Sect. 8(b) Inventory	CUMENE	98-82-8
Inventory - TSCA - Sect. 8(b) Inventory	ETHYL BENZENE	100-41-4
Inventory - TSCA - Sect. 8(b) Inventory	HYDRODESULFURIZED	64742-81-0
	KEROSENE	
Inventory - TSCA - Sect. 8(b) Inventory	N-HEXANE	110-54-3
Inventory - TSCA - Sect. 8(b) Inventory	NAPHTHALENE	91-20-3
Inventory - TSCA - Sect. 8(b) Inventory	TOLUENE	108-88-3
Inventory - TSCA - Sect. 8(b) Inventory	XYLENE	1330-20-7
Massachusetts - Right To Know List	BENZENE	71-43-2
Massachusetts - Right To Know List	CUMENE	98-82-8
Massachusetts - Right To Know List	ETHYL BENZENE	100-41-4
Massachusetts - Right To Know List	N-HEXANE	110-54-3
Massachusetts - Right To Know List	NAPHTHALENE	91-20-3
Massachusetts - Right To Know List	TOLUENE	108-88-3

Massachusetts - Right To Know List	XYLENE	1330-20-7
New Jersey - Department of Health RTK List	BENZENE	71-43-2
New Jersey - Department of Health RTK List	CUMENE	98-82-8
New Jersey - Department of Health RTK List	ETHYL BENZENE	100-41-4
New Jersey - Department of Health RTK List	N-HEXANE	110-54-3
New Jersey - Department of Health RTK List	NAPHTHALENE	91-20-3
New Jersey - Department of Health RTK List	TOLUENE	108-88-3
New Jersey - Department of Health RTK List	XYLENE	1330-20-7
New Jersey - Env Hazardous Substances List	BENZENE	71-43-2
New Jersey - Env Hazardous Substances List	CUMENE	98-82-8
New Jersey - Env Hazardous Substances List	ETHYL BENZENE	100-41-4
New Jersey - Env Hazardous Substances List	N-HEXANE	110-54-3
New Jersey - Env Hazardous Substances List	NAPHTHALENE	91-20-3
New Jersey - Env Hazardous Substances List	TOLUENE	108-88-3
New Jersey - Env Hazardous Substances List	XYLENE	1330-20-7
New Jersey - Special Hazardous Substances	BENZENE	71-43-2
New Jersey - Special Hazardous Substances	CUMENE	98-82-8
New Jersey - Special Hazardous Substances	ETHYL BENZENE	100-41-4
New Jersey - Special Hazardous Substances	N-HEXANE	110-54-3
New Jersey - Special Hazardous Substances	NAPHTHALENE	91-20-3
New Jersey - Special Hazardous Substances	TOLUENE	108-88-3
New Jersey - Special Hazardous Substances	XYLENE	1330-20-7
NTP - Report on Carcinogens - Known Carcinogens	BENZENE	71-43-2
NTP - Report on Carcinogens - Suspect Carcinogens	NAPHTHALENE	91-20-3
OSHA - Final PELs - Ceiling Limits	BENZENE	71-43-2
OSHA - Final PELs - Ceiling Limits	TOLUENE	108-88-3
OSHA - Final PELs - Short Term Exposure Limits	BENZENE	71-43-2
OSHA - Final PELs - Skin Notations	CUMENE	98-82-8
OSHA - Final PELs - Time Weighted Averages	BENZENE	71-43-2
OSHA - Final PELs - Time Weighted Averages	CUMENE	98-82-8
OSHA - Final PELs - Time Weighted Averages	ETHYL BENZENE	100-41-4
OSHA - Final PELs - Time Weighted Averages	N-HEXANE	110-54-3
OSHA - Final PELs - Time Weighted Averages	NAPHTHALENE	91-20-3
OSHA - Final PELs - Time Weighted Averages	TOLUENE	108-88-3
OSHA - Final PELs - Time Weighted Averages	XYLENE	1330-20-7
OSHA - Hazard Communication Carcinogens	BENZENE	71-43-2
OSHA - Hazard Communication Carcinogens	ETHYL BENZENE	100-41-4
OSHA - Hazard Communication Carcinogens	NAPHTHALENE	91-20-3
OSHA - Specifically Regulated Carcinogens	BENZENE	71-43-2
Pennsylvania - RTK (Right to Know) List	BENZENE	71-43-2
Pennsylvania - RTK (Right to Know) List	CUMENE	98-82-8
Pennsylvania - RTK (Right to Know) List	ETHYL BENZENE	100-41-4
Pennsylvania - RTK (Right to Know) List	N-HEXANE	110-54-3
Pennsylvania - RTK (Right to Know) List	NAPHTHALENE	91-20-3
Pennsylvania - RTK (Right to Know) List	TOLUENE	108-88-3
Pennsylvania - RTK (Right to Know) List	XYLENE	1330-20-7
Pennsylvania - RTK - Environmental Hazard List	BENZENE	71-43-2
Pennsylvania - RTK - Environmental Hazard List	CUMENE	98-82-8
Pennsylvania - RTK - Environmental Hazard List	ETHYL BENZENE	100-41-4
Pennsylvania - RTK - Environmental Hazard List	NAPHTHALENE	91-20-3
Pennsylvania - RTK - Environmental Hazard List	TOLUENE	108-88-3
Pennsylvania - RTK - Environmental Hazard List	XYLENE	1330-20-7
Pennsylvania - RTK - Special Hazardous Substances	BENZENE	71-43-2
TSCA - Sect. 12(b) - Export Notification	NAPHTHALENE	91-20-3
TSCA - Section 4 - Chemical Test Rules	NAPHTHALENE	91-20-3
U.S. - DOT - Hazardous Substances and RQs (App A)	BENZENE	71-43-2
U.S. - DOT - Hazardous Substances and RQs (App A)	CUMENE	98-82-8
U.S. - DOT - Hazardous Substances and RQs (App A)	ETHYL BENZENE	100-41-4
U.S. - DOT - Hazardous Substances and RQs (App A)	N-HEXANE	110-54-3
U.S. - DOT - Hazardous Substances and RQs (App A)	NAPHTHALENE	91-20-3
U.S. - DOT - Hazardous Substances and RQs (App A)	TOLUENE	108-88-3
U.S. - DOT - Hazardous Substances and RQs (App A)	XYLENE	1330-20-7

Title III Classifications Sections 311,312:

- Acute: **YES**
- Chronic: **YES**
- Fire: **YES**
- Reactivity: **NO**
- Sudden Release of Pressure: **NO**

16. OTHER INFORMATION

Dermal exposure to middle distillates have caused skin irritation and skin cancer in laboratory animals when repeatedly applied and left in place between applications. Studies to further evaluate the carcinogenic potential of middle distillates are currently underway. COMPONENT TOXICITY: Overexposure to naphthalene, a minor component of this product, may cause skin, eye and respiratory tract irritation, anemia, loss of vision, nervous system effects and kidney and thymus damage. Also, exposure to naphthalene has produced "respiratory tract" tumors in laboratory animals. Intentional misuse (sniffing) can cause damage to the brain, liver and kidneys and may cause sudden death.