

**DA6282 AFFIX HEAVY DUTY ADHESIVE**

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : AFFIX HEAVY DUTY ADHESIVE

Material number : DA6282

**Manufacturer or supplier's details**

Company : Lawson Products, Inc.

Address : 8770 W. Bryn Mawr Ave., Suite 900  
Chicago, IL 60631

Telephone : 773-304-5050

**Emergency telephone numbers: 888-426-4851****SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	light yellow
Odour	solvent-like

**GHS Classification**Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

### **Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### **Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

## Potential Health Effects

### **Carcinogenicity:**

#### **IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### **ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### **OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

### Hazardous components

Chemical Name	CAS-No.	Concentration [%]
propane	74-98-6	>= 20 - < 30
acetone	67-64-1	>= 20 - < 30
butane	106-97-8	>= 10 - < 20
Heptane, branched, cyclic and linear	426260-76-6	>= 10 - < 20
methyl acetate	79-20-9	>= 5 - < 10

### SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Get medical attention if irritation develops and persists.  
Wash contaminated clothing before re-use.  
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.  
Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Keep respiratory tract clear.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical  
Water spray jet  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Refer to protective measures listed in sections 7 and 8.  
Remove all sources of ignition.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent further leakage or spillage.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Always replace cap after use.  
Do not breathe vapours or spray mist.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong oxidizing agents

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
Heptane, branched, cyclic and linear	426260-76-6	TWA	85 ppm 350 mg/m <sup>3</sup>	NIOSH REL
		C	440 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
methyl acetate	79-20-9	STEL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA P0
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 760 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 610 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 ppm 610 mg/m <sup>3</sup>	OSHA P0
		STEL	250 ppm 760 mg/m <sup>3</sup>	OSHA P0

#### Biological occupational exposure limits

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Remarks : Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses  
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : light yellow

Odour : solvent-like

Odour Threshold : no data available

pH : no data available

Melting point/freezing point : no data available

Boiling point : not applicable

Flash point :  
not applicable

Evaporation rate : no data available

Flammability (solid, gas) : Extremely flammable aerosol.

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: no data available
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Heat of combustion	: 40.94 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Nitrogen oxides (NOx)

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

no data available

#### Skin corrosion/irritation

##### Product:

Remarks: May cause skin irritation in susceptible persons.

#### Serious eye damage/eye irritation

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

**Product:**

Remarks: Irritating to eyes.

**Respiratory or skin sensitisation**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

no data available

**Reproductive toxicity**

no data available

**propane:**

**acetone:**

**butane:**

**Heptane, branched, cyclic and linear:**

**methyl acetate:**

**STOT - single exposure**

no data available

**STOT - repeated exposure**

no data available

**Aspiration toxicity**

no data available

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

no data available

**Persistence and degradability**

no data available

**Bioaccumulative potential**

**Product:**

Partition coefficient: n-octanol/water : Remarks: no data available



# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

### Components:

#### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

### **Mobility in soil**

no data available

### **Other adverse effects**

no data available

### Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues

: Dispose of in accordance with local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging

: Do not burn, or use a cutting torch on, the empty drum. Dispose of as unused product. Empty remaining contents. Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
This material is not classified.

Transportation Regulation: IMDG (Vessel):  
This material is not classified.

Transportation Regulation: IATA (Cargo Air):  
This material is not classified.

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

Transportation Regulation: IATA (Passenger Air):  
This material is not classified.

Transportation Regulation: TDG (Canada):  
This material is not classified.

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### The components of this product are reported in the following inventories:

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL.  
**AICS** Not in compliance with the inventory  
**NZIoC** Not in compliance with the inventory  
**PICCS** On the inventory, or in compliance with the inventory  
**IECSC** Not in compliance with the inventory

#### Inventory Acronym and Validity Area Legend:

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015


Print Date 04/17/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



##### HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

#### OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves.

**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

# SAFETY DATA SHEET

## A00315 LAWSON AFFIX ADHESIVE 20N12

Version 1.0

Revision Date 02/18/2015

Print Date 04/17/2015

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.