

Safety Data Sheet

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • **Repair Sealer**
Product Code • 94-393

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Adhesive/sealing compound

1.3 Details of the supplier of the safety data sheet

Manufacturer • Patch Rubber Company
 100 Patch Rubber Road
 Weldon, NC 27890
 United States

Telephone (General) • (252)-536-2574

Responsible party • Christian Gimenez
 Intertek Analytical Services France
 France

Telephone (Technical) • 33 (0) 6 07 11 22 15

1.4 Emergency telephone number

Manufacturer • 1-800-424-9300 - CHEMTREC

Manufacturer • +1 703-527-3887 - CHEMTREC - Outside USA & CANADA (collect calls accepted)

Section 2: Hazards Identification

EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP

- Flammable Liquids 2 - H225
- Skin Irritation 2 - H315
- Skin Sensitization 1A - H317
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
- Hazardous to the aquatic environment Acute 1 - H400
- Hazardous to the aquatic environment Chronic 1 - H410

DSD/DPD

- Highly Flammable (F)
- Dangerous to the Environment (N)
- Harmful (Xn)
- Irritant (Xi)
- R11, R50, R53, R38, R67

2.2 Label Elements

CLP

DANGER



- H225 - Highly flammable liquid and vapour
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H336 - May cause drowsiness or dizziness
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements

- Prevention**
- P102 - Keep out of reach of children.
 - P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - P272 - Contaminated work clothing should not be allowed out of the workplace.
 - P273 - Avoid release to the environment.
 - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- P370+P378 - In case of fire: Use appropriate media for extinction.
- Storage/Disposal**
- P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



- Risk phrases**
- R11 - Highly flammable.
 - R50 - Very toxic to aquatic organisms.
 - R53 - May cause long-term adverse effects in the aquatic environment.
 - R38 - Irritating to skin.
 - R67 - Vapours may cause drowsiness and dizziness.
- Safety phrases**
- S2 - Keep out of reach of children.
 - S9 - Keep container in a well ventilated place
 - S16 - Keep away from sources of ignition - No Smoking.
 - S29 - Do not empty into drains.
 - S33 - Take precautionary measures against static discharges.
 - S60 - This material and its container must be disposed of as hazardous waste.
 - S62 - If swallowed, do not induce vomiting. Seek medical advice immediately and show the container or label.

2.3 Other Hazards

CLP

- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.
The components of this material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications of the components do not apply to the material.

DSD/DPD

- According to European Directive 1999/45/EC this preparation is considered dangerous.

UN GHS

According to Third Revised Edition

2.1 Classification of the substance or mixture

UN GHS

- Flammable Liquids 2 - H225
- Skin Irritation 2 - H315
- Skin Sensitization 1A - H317
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Hazardous to the aquatic environment Acute 1 - H400
 Hazardous to the aquatic environment Chronic 1 - H410

2.2 Label elements

UN GHS

DANGER



- H225 - Highly flammable liquid and vapour
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H336 - May cause drowsiness or dizziness
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - P233 - Keep container tightly closed.
 - P235 - Keep cool.
 - P240 - Ground and/or bond container and receiving equipment.
 - P241 - Use explosion-proof - electrical, ventilating and/or lighting equipment.
 - P242 - Use only non-sparking tools.
 - P243 - Take precautionary measures against static discharge.
 - P261 - Avoid breathing dust, fume, gas, mist, vapours and/or spray.
 - P264 - Wash thoroughly after handling.
 - P271 - Use only outdoors or in a well-ventilated area.
 - P272 - Contaminated work clothing should not be allowed out of the workplace.
 - P273 - Avoid release to the environment.
 - P280 - Wear protective gloves and eye/face protection , .
- Response**
- P370+P378 - In case of fire: Use appropriate media for extinction.
 - P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 - P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
 - P363 - Wash contaminated clothing before reuse.
 - P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 - P321 - Specific treatment, see supplemental first aid information.
 - P391 - Collect spillage.
- Storage/Disposal**
- P403+P235 - Store in a well-ventilated place. Keep cool.
 - P405 - Store locked up.
 - P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

UN GHS

- According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS

- Flammable Liquid
- Flammable/Combustible Class IB
- Irritant
- Target Organ Effects - Central Nervous System (CNS)

2.2 Label elements

OSHA HCS

- No label element(s) required.

2.3 Other hazards

OSHA HCS

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS




- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information



See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance according to United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
				UN GHS: Flam Liq. 2; Asp. Tox 1; Skin Irrit.	

Naphtha (petroleum), hydrotreated light	CAS: 64742-49-0 EC Number: 265-151-9	60% TO 100%	NDA	2; STOT SE 3: Narc.; Aquatic Acute 1; Aquatic Chronic 1 EU DSD/DPD: Annex I - Carc.Cat.2; R45; Muta.Cat.2; R46; Xn; R65 EU CLP: Annex VI - Carc. 1B H350, Muta. 1B H340; Asp Tox 1 H304	NDA
Carbon Black	CAS: 1333-86-4 EC Number: 215-609-9	7% TO 13%	Ingestion/Oral-Rat LD50 · >15400 mg/kg Skin-Rabbit LD50 · >3 g/kg	UN GHS: Skin Irrit 2, STOT SE 3, Carc. 2 EU DSD/DPD: Self Classified Carc. Cat 3 EU CLP: Self Classified Carc. 2A H351	NDA
Benzothiazole, 2,2'-dithiobis-	CAS: 120-78-5 EC Number: 204-424-9	0.1% TO 1%	Ingestion/Oral-Rat LD50 · >12 g/kg Skin-Rabbit LD50 · >7940 mg/kg	UN GHS: Skin Sens. 1; EU DSD/DPD: Annex I - R31, R43, N R50-53 EU CLP: Annex VI - Skin Sens. 1 H317; Aquatic Acute 1 H400; Aquatic Chronic 1 H410	NDA
Stearic acid	CAS: 57-11-4 EC Number: 200-313-4	0.1% TO 1%	Skin-Rabbit LD50 · >5 g/kg Ingestion/Oral-Rat LD50 · 4600 mg/kg	UN GHS: Acute Tox 5 (oral); Skin Irrit. 2 EU DSD/DPD: Self Classified - Xi R38 EU CLP: Self Classified - Skin Irrit. 2	NDA
Zinc oxide	CAS: 1314-13-2 EC Number: 215-222-5	0.1% TO 1%	NDA	UN GHS: Aquatic Acute 1; Aquatic Chronic 1 EU DSD/DPD: Annex I - N R50-53 EU CLP: Annex VI - Aquatic Acute 1 H400; Aquatic Chronic H410	NDA
Propionic acid	CAS: 79-09-4 EC Number: 201-176-3 UN: UN1848	< 0.1%	Ingestion/Oral-Rat LD50 · 2600 mg/kg Skin-Rabbit LD50 · 500 µL/kg	UN GHS: Eye Dam. 1A; Skin Corr. 1A; STOT SE 3: Resp Irrit.; Aquatic Acute 3 EU DSD/DPD: Annex I - C; R34 EU CLP: Annex VI - Skin Corr 1B H335	NDA
Sulfur	CAS: 7704-34-9 EC Number: 231-722-6 UN: UN1350, UN2448	< 0.1%	NDA	UN GHS: Skin Irrit 2, Eye Irrit 2A, STOT SE 3: Resp Irrit.; EU DSD/DPD: Annex I - Xi R38 EU CLP: Annex VI - Skin Irrit 2 H315	NDA

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.

Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

Eye

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do NOT induce vomiting. If person is drowsy or unconscious and vomiting, place on the left side with head down. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- May cause skin irritation. Inhalation of vapors or fumes will cause central nervous system effects with symptoms of dizziness, drowsiness, lethargy, coma and death.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

- Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to the material.

4.4 Other information

- Call 911 or emergency medical service. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Keep victim warm and quiet.

See Section 2 for Potential Health Effects.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • Carbon dioxide (CO₂), water fog, dry chemical or chemical foam.

Unsuitable Extinguishing Media • Avoid the use of streaming water, as this may spread the fire.

Firefighting Procedures • Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards • HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Extremely flammable liquid and vapor. Vapors may form explosive mixtures with air. Vapor explosion hazard indoors, outdoors or in sewers. Vapors may travel to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products • Smoke, soot, fumes or vapors, oxides of carbon.

5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear positive pressure self-contained breathing apparatus (SCBA). Runoff from fire control may cause pollution. LARGE FIRES: Dike fire-control water for later disposal.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions • Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate enclosed areas.

Emergency Procedures • As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Keep out of low areas. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Avoid run off to waterways and sewers.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures • Stop leak if you can do it without risk. All equipment used when handling the product must be grounded.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
 Use clean non-sparking tools to collect absorbed material.
 A vapor suppressing foam may be used to reduce vapors.
 LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Keep away from heat and ignition sources – No Smoking. Product can accumulate static charge by flow or agitation. Bond and ground equipment when transferring from one vessel to another. Empty containers retain product residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks or other ignition sources. They may explode and cause injury or death. Use only with adequate ventilation. Do not enter confined spaces such as tanks or pits without following proper entry procedures.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Keep container closed when not in use. Keep away from incompatible materials.
- Keep away from heat, ignition sources oxidizers and strong acids.

Incompatible Materials or Ignition Sources

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	Europe	France
Methylcyclohexane (108-87-2)	TWAs	400 ppm TWA	400 ppm TWAEV; 1600 mg/m3 TWAEV	400 ppm TWAEV; 1610 mg/m3 TWAEV	Not established	400 ppm VME; 1600 mg/m3 VME
3-Methylhexane (589-34-4)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Hexane, 2-methyl- (591-76-4)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Pentane, 2,3-dimethyl- (565-59-3)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Ethylbenzene (100-41-4)	STELs	125 ppm STEL	125 ppm STEV; 540 mg/m3 STEV	125 ppm STEV; 543 mg/m3 STEV	Not established	100 ppm VLCT (restrictive limit); 442 mg/m3 VLCT (restrictive limit)
	TWAs	100 ppm TWA	100 ppm TWAEV; 435 mg/m3 TWAEV	100 ppm TWAEV; 434 mg/m3 TWAEV	Not established	20 ppm VME (restrictive limit); 88.4 mg/m3 VME (restrictive limit)
			2.5 ppm STEV			

Benzene (71-43-2)	STELs	2.5 ppm STEL	(applies to workplaces to which the designated substance regulation does not apply); 2.5 ppm STEV (designated substances regulation)	5 ppm STEV; 15.5 mg/m3 STEV	Not established	Not established
	TWAs	0.5 ppm TWA	0.5 ppm TWAEV (applies to workplaces to which the designated substance regulation does not apply); 0.5 ppm TWAEV (designated substance regulation)	1 ppm TWAEV; 3 mg/m3 TWAEV	Not established	1 ppm VME (restrictive limit); 3.25 mg/m3 VME (restrictive limit)
Toluene (108-88-3)	STELs	Not established	Not established	Not established	100 ppm STEL; 384 mg/m3 STEL	100 ppm VLCT (restrictive limit); 384 mg/m3 VLCT (restrictive limit)
	TWAs	20 ppm TWA	20 ppm TWAEV	50 ppm TWAEV; 188 mg/m3 TWAEV	50 ppm TWA; 192 mg/m3 TWA	50 ppm VME (restrictive limit); 192 mg/m3 VME (restrictive limit)
Propionic acid (79-09-4)	TWAs	10 ppm TWA	10 ppm TWAEV; 30 mg/m3 TWAEV	10 ppm TWAEV; 30 mg/m3 TWAEV	Not established	10 ppm VME (indicative limit); 31 mg/m3 VME (indicative limit)
	STELs	Not established	Not established	Not established	Not established	20 ppm VLCT (indicative limit); 62 mg/m3 VLCT (indicative limit)
Zinc oxide (1314-13-2)	STELs	10 mg/m3 STEL (respirable fraction)	10 mg/m3 STEV (respirable)	10 mg/m3 STEV (fume)	Not established	Not established
	TWAs	2 mg/m3 TWA (respirable fraction)	2 mg/m3 TWAEV (respirable)	5 mg/m3 TWAEV (fume); 10 mg/m3 TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	Not established	5 mg/m3 VME (fume); 10 mg/m3 VME (dust)
Carbon Black (1333-86-4)	TWAs	3.5 mg/m3 TWA	3.5 mg/m3 TWAEV	3.5 mg/m3 TWAEV	Not established	3.5 mg/m3 VME
Heptane (142-82-5)	STELs	500 ppm STEL	500 ppm STEV; 2045 mg/m3 STEV	500 ppm STEV; 2050 mg/m3 STEV	Not established	500 ppm VLCT (restrictive limit); 2085 mg/m3 VLCT (restrictive limit)
	TWAs	400 ppm TWA	400 ppm TWAEV; 1635 mg/m3 TWAEV	400 ppm TWAEV; 1640 mg/m3 TWAEV	Not established	400 ppm VME (restrictive limit); 1668 mg/m3 VME (restrictive limit)

Exposure Limits/Guidelines (Con't.)				
	Result	Italy	NIOSH	OSHA
Methylcyclohexane (108-87-2)	TWAs	Not established	400 ppm TWA; 1600 mg/m3 TWA	500 ppm TWA; 2000 mg/m3 TWA
Ethylbenzene (100-41-4)	STELs	200 ppm STEL; 884 mg/m3 STEL	125 ppm STEL; 545 mg/m3 STEL	Not established
	TWAs	100 ppm TWA; 442 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
Benzene (71-43-2)	TWAs	1 ppm TWA; 3.25 mg/m3 TWA	0.1 ppm TWA	10 ppm TWA (applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028); 1 ppm TWA
	Ceilings	Not established	Not established	25 ppm Ceiling
	STELs	Not established	1 ppm STEL	5 ppm STEL (see 29 CFR 1910.1028)
Toluene (108-88-3)	TWAs	192 ppm TWA; 50 mg/m3 TWA	100 ppm TWA; 375 mg/m3 TWA	200 ppm TWA
	Ceilings	Not established	Not established	300 ppm Ceiling
	STELs	Not established	150 ppm STEL; 560 mg/m3 STEL	Not established
Propionic acid (79-09-4)	STELs	20 ppm STEL; 62 mg/m3 STEL	15 ppm STEL; 45 mg/m3 STEL	Not established
	TWAs	10 ppm TWA; 31 mg/m3 TWA	10 ppm TWA; 30 mg/m3 TWA	Not established
Zinc oxide (1314-13-2)	TWAs	Not established	5 mg/m3 TWA (dust and fume)	5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
	Ceilings	Not established	15 mg/m3 Ceiling (dust)	Not established
	STELs	Not established	10 mg/m3 STEL (fume)	Not established
Carbon Black (1333-86-4)	TWAs	Not established	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (carbon black in presence of polycyclic aromatic hydrocarbons, as PAH)	3.5 mg/m3 TWA
Heptane (142-82-5)	TWAs	500 ppm TWA; 2085 mg/m3 TWA	85 ppm TWA; 350 mg/m3 TWA	500 ppm TWA; 2000 mg/m3 TWA
	Ceilings	Not established	440 ppm Ceiling (15 min); 1800 mg/m3 Ceiling (15 min)	Not established

8.2 Exposure controls

Engineering Measures/Controls

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable exposure limit values.

Personal Protective Equipment

Pictograms



Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety goggles.

Hands

- Wear protective gloves -neoprene, butyl or nitrile rubber with cuffs.

Skin/Body

- Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

General Industrial Hygiene Considerations

- Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Avoid release to the environment.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

VME = Valeur Moyenne d'Exposition is the maximum permissible concentration for a work day

VLCT = Valeurs limites d'exposition à court terme is the short-term exposure limit based on 15-minute exposure.

MSHA = Mine Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Black flammable liquid with a hydrocarbon odor.
Color	Black	Odor	Hydrocarbon
Taste	Data lacking	Particulate Type	Data lacking
Particulate Size	Data lacking	Aerosol Type	Data lacking
Odor Threshold	Data lacking	Physical and Chemical Properties	Data lacking
General Properties			
Boiling Point	93.3 C(199.94 F)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	Heat of Decomposition	Data lacking
pH	Data lacking	Specific Gravity/Relative Density	0.824 Water=1
Density	6.8 lbs/gal	Bulk Density	Data lacking
Water Solubility	Negligible	Solvent Solubility	Data lacking
Viscosity	2000 to 6000 Centipoise (cPs, cP) or mPas	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	45 mmHg (torr) @ 20 C(68 F)	Vapor Density	3.5 Air=1
Evaporation Rate	4.2 n-Butyl Acetate = 1	VOC (Wt.)	Data lacking
VOC (Vol.)	520 g/L	Volatiles (Wt.)	Data lacking

Volatiles (Vol.)	Data lacking		
Flammability			
Flash Point	-10 C(14 F)	UEL	7 %
LEL	1 %	Autoignition	223 C(433.4 F)
Self-Accelerating Decomposition Temperature (SADT)	Data lacking	Heat of Combustion (ΔH_c)	Data lacking
Burning Time	Data lacking	Flame Duration	Data lacking
Flame Height	Data lacking	Flame Extension	Data lacking
Ignition Distance	Data lacking	Flammability (solid, gas)	Data lacking
Environmental			
Half-Life	Data lacking	Octanol/Water Partition coefficient	Data lacking
Coefficient of water/oil distribution	Data lacking	Bioaccumulation Factor	Data lacking
Bioconcentration Factor	Data lacking	Biochemical Oxygen Demand BOD/BOD5	Data lacking
Chemical Oxygen Demand	Data lacking	Persistence	Data lacking
Degradation	Data lacking		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- High temperatures, sparks, open flames and live electrical circuits.

10.5 Incompatible materials

- Oxidizing agents, strong acids.

10.6 Hazardous decomposition products

- In case of fire oxides of carbon, hydrocarbons, fumes or vapors, soot and smoke may be produced.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
Carbon Black (7% TO 13%)	1333-86-4	Acute Toxicity: orl-rat LD50:>15400 mg/kg; ihl-rat TCLo:1 mg/m3/13W-I; ihl-rat TCLo:50 mg/m3/13W-I; skn-rbt LD50:>3 gm/kg; Mutagen: dnd-rat-ihl 50 ug/L/13W-I; Tumorigen/Carcinogen: ihl-rat TCLo:11600 ug/m3/18H/2Y-I
Benzothiazole, 2,2'-dithiobis-(0.1% TO 1%)	120-78-5	Acute Toxicity: orl-rat LD50:>12 gm/kg; skn-rbt LD50:>7940 mg/kg
Stearic acid (0.1% TO 1%)	57-11-4	Acute Toxicity: orl-rat LD50:4600 mg/kg; skn-rbt LD50:>5 gm/kg; Irritation: skn-rbt 500 mg/24H MOD
Zinc oxide (0.1% TO 1%)	1314-13-2	Acute Toxicity: ihl-rat TCLo:25 mg/m3/3H; Irritation: eye-rbt 500 mg/24H MLD; skn-rbt 500 mg/24H MLD; Reproductive: orl-rat TDLo:6846 mg/kg (1-22D preg)
Propionic acid (< 0.1%)	79-09-4	Acute Toxicity: orl-rat TDLo:550 gm/kg/110D-C; skn-rbt LD50:500 uL/kg; Irritation: eye-rbt 990 ug SEV; skn-rbt 495 mg open SEV
Sulfur (< 0.1%)	7704-34-9	Acute Toxicity: orl-rbt LDLo:175 mg/kg; Irritation: eye-hmn 8 ppm

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 UN GHS • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Skin sensitization	EU/CLP • Skin Sensitizer 1A UN GHS • Skin Sensitizer 1A
Respiratory sensitization	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects UN GHS • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
STOT-RE	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met

Target Organs

- Central Nervous System (CNS)

Route(s) of entry/exposure

- Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- High concentrations may cause irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death. Intentional concentration and inhalation of heptane vapors may lead to nervous system damage.

Chronic (Delayed)

- No data available.

Skin

Acute (Immediate)

- Causes skin irritation. Direct skin contact with heptane may cause pain, burning, and itching. May cause skin sensitization. Symptoms include redness, and skin rash.

Chronic (Delayed)

- Repeated and prolonged exposure may cause dermatitis.

Eye

Acute (Immediate)

- Causes eye irritation.

Chronic (Delayed)

- No data available.

Ingestion

Acute (Immediate)

- May cause irritation if swallowed.

Chronic (Delayed)

- No data available.

Carcinogenic Effects

- This product contains carbon black (encapsulated)(1333-86-4). According to IARC "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint."

Carcinogenic Effects		
	CAS	IARC
Carbon Black	1333-86-4	Group 2B-Possible Carcinogen

Section 12 - Ecological Information

12.1 Toxicity

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been carried out.

12.6 Other adverse effects

- No studies have been found.

12.7 Other Information

- No data is available on the adverse effects of this material on the environment. Contains 60-100% of a component that has aquatic toxicity values that are expected to be in the range of 1 - 10 mg/l (based upon data from components and similar products).

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives, containing a flammable liquid	3	II	NDA
TDG	UN1133	ADHESIVES containing flammable liquid	3	II	NDA
IMO/IMDG	UN1133	ADHESIVES containing flammable liquid	3	II	Severe Marine Pollutant
ADN	UN1133	ADHESIVES containing flammable liquid (vapour pressure at 50 °C not more than 110 kPa)	3	II	Marine Pollutant
ADR/RID	UN1133	ADHESIVES containing flammable liquid (vapour pressure at 50 C not more than 110 kPa)	3	II	Marine Pollutant
IATA/ICAO	UN1133	Adhesives containing flammable liquid	3	II	Acute Aquatic Toxicity, Chronic Aquatic Toxicity

14.6 Special precautions for user • None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
Naphtha (petroleum), hydrotreated light	64742-49-0	No	No	No
Heptane	142-82-5	Yes	Yes	Yes
3-Methylhexane	589-34-4	Yes	Yes	Yes
Methylcyclohexane	108-87-2	Yes	Yes	Yes
Hexane, 2-methyl-	591-76-4	Yes	No	Yes
Carbon Black	1333-86-4	Yes	Yes	Yes
3-Ethylpentane	617-78-7	No	No	No
Pentane, 2,3-dimethyl-	565-59-3	Yes	Yes	Yes
Benzothiazole, 2,2'-dithiobis-	120-78-5	No	No	No
Stearic acid	57-11-4	No	No	No

Zinc oxide	1314-13-2	Yes	Yes	Yes
White mineral oil	8042-47-5	No	No	No
Solvent-refined residual-oils (highly refined)	64742-01-4	No	No	No
Rosin ester	64365-17-9	No	No	No
Propionic acid	79-09-4	Yes	Yes	Yes
Sulfur	7704-34-9	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes
Benzene	71-43-2	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Naphtha (petroleum), hydrotreated light	64742-49-0	Yes	No	Yes	No	Yes
Heptane	142-82-5	Yes	No	Yes	No	Yes
3-Methylhexane	589-34-4	No	Yes	Yes	No	Yes
Methylcyclohexane	108-87-2	Yes	No	Yes	No	Yes
Hexane, 2-methyl-	591-76-4	Yes	No	Yes	No	Yes
Carbon Black	1333-86-4	Yes	No	Yes	Yes	Yes
3-Ethylpentane	617-78-7	No	No	Yes	No	No
Pentane, 2,3-dimethyl-	565-59-3	No	Yes	Yes	No	Yes
Benzothiazole, 2,2'-dithiobis-	120-78-5	Yes	No	Yes	No	Yes
Stearic acid	57-11-4	Yes	No	Yes	No	Yes
Zinc oxide	1314-13-2	Yes	No	Yes	No	Yes
White mineral oil	8042-47-5	Yes	No	Yes	No	Yes
Solvent-refined residual-oils (highly refined)	64742-01-4	Yes	No	Yes	No	Yes
Rosin ester	64365-17-9	Yes	No	Yes	No	Yes
Propionic acid	79-09-4	Yes	No	Yes	No	Yes
Sulfur	7704-34-9	Yes	No	Yes	No	Yes
Toluene	108-88-3	Yes	No	Yes	No	Yes
Benzene	71-43-2	Yes	No	Yes	No	Yes
Ethylbenzene	100-41-4	Yes	No	Yes	No	Yes

Canada

Labor
 Canada - WHMIS - Classifications of Substances

● Stearic acid	57-11-4	0.1% TO 1%	Uncontrolled product according to WHMIS classification criteria
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	B2
● 3-Methylhexane	589-34-4	0% TO 30%	B2
● Hexane, 2-methyl-	591-76-4	0% TO 15%	B2
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	B3, D1B, E
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Carbon Black, non-respirable on Health Canada's WHMIS website.)
● Ethylbenzene	100-41-4	< 0.001%	B2, D2A, D2B
● Heptane	142-82-5	30% TO 45%	B2, D2B
● Toluene	108-88-3	< 0.05%	B2, D2A, D2B
● Zinc oxide	1314-13-2	0.1% TO 1%	Uncontrolled product according to WHMIS classification criteria
● Benzene	71-43-2	< 0.001%	B2, D2A, D2B
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Uncontrolled product according to WHMIS classification criteria
● Sulfur	7704-34-9	< 0.1%	B4
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	B2
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

Canada - WHMIS - Ingredient Disclosure List

● Stearic acid	57-11-4	0.1% TO 1%	1 %
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	1 %
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	1 %
● Propionic acid	79-09-4	< 0.1%	1 %
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	1 %
● Ethylbenzene	100-41-4	< 0.001%	0.1 %
● Heptane	142-82-5	30% TO 45%	1 %
● Toluene	108-88-3	< 0.05%	1 %
● Zinc oxide	1314-13-2	0.1% TO 1%	1 %
● Benzene	71-43-2	< 0.001%	0.1 %
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

Environment

Canada - CEPA - Priority Substances List

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
----------------	---------	------------	------------

• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Priority Substance List 1 (substance not considered toxic)
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	Priority Substance List 1 (substance considered toxic)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65
• Methylcyclohexane	108-87-2	0% TO 20%	F; R11 Xi; R38 N; R51 R53 Xn; R65 R67
• 3-Methylhexane	589-34-4	0% TO 30%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Hexane, 2-methyl-	591-76-4	0% TO 15%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	R31 R43 N; R50 R53
• Propionic acid	79-09-4	< 0.1%	C; R34
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Carc.Cat.2; R45
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	F; R11 Xn; R20
• Heptane	142-82-5	30% TO 45%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Toluene	108-88-3	< 0.05%	F; R11 Xi; R38 Xn; R48/20 R65 Repr.Cat.3; R63 R67
• Zinc oxide	1314-13-2	0.1% TO 1%	N; R50 R53
• Benzene	71-43-2	< 0.001%	F; R11 Xi; R36/38 Carc.Cat.1; R45 Muta.Cat.2; R46 T; R48/23/24/25 Xn; R65
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Xi; R38
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• 3-Ethylpentane	617-78-7	0% TO 5%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	25%<=C: C; R34 10%<=C<25%: Xi; R36/37/38
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	T R:45-46-65 S:53-45
● Methylcyclohexane	108-87-2	0% TO 20%	F Xn N R:11-38-51/53-65-67 S:(2)-9-16-33-61-62
● 3-Methylhexane	589-34-4	0% TO 30%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
● Hexane, 2-methyl-	591-76-4	0% TO 15%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Xi N R:31-43-50/53 S:(2)-36/37-60-61
● Propionic acid	79-09-4	< 0.1%	C R:34 S:(1/2)-23-36-45
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	T R:45 S:53-45
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	F Xn R:11-20 S:(2)-16-24/25-29
● Heptane	142-82-5	30% TO 45%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
● Toluene	108-88-3	< 0.05%	F Xn R:11-38-48/20-63-65-67 S:(2)-36/37-46-62
● Zinc oxide	1314-13-2	0.1% TO 1%	N R:50/53 S:60-61
● Benzene	71-43-2	< 0.001%	F T R:45-46-11-36/38-48/23/24/25-65 S:53-45
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Xi R:38 S:(2)-46
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
● 3-Ethylpentane	617-78-7	0% TO 5%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	H, P
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed

● 3-Methylhexane	589-34-4	0% TO 30%	C
● Hexane, 2-methyl-	591-76-4	0% TO 15%	C
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	B
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	H, L
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	30% TO 45%	C
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	E
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	C
● 3-Ethylpentane	617-78-7	0% TO 5%	C

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	S:53-45
● Methylcyclohexane	108-87-2	0% TO 20%	S:(2)-9-16-33-61-62
● 3-Methylhexane	589-34-4	0% TO 30%	S:(2)-9-16-29-33-60-61-62
● Hexane, 2-methyl-	591-76-4	0% TO 15%	S:(2)-9-16-29-33-60-61-62
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	S:(2)-36/37-60-61
● Propionic acid	79-09-4	< 0.1%	S:(1/2)-23-36-45
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	S:53-45
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	S:(2)-16-24/25-29
● Heptane	142-82-5	30% TO 45%	S:(2)-9-16-29-33-60-61-62
● Toluene	108-88-3	< 0.05%	S:(2)-36/37-46-62
● Zinc oxide	1314-13-2	0.1% TO 1%	S:60-61
● Benzene	71-43-2	< 0.001%	S:53-45
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	S:(2)-46
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	S:(2)-9-16-29-33-60-61-62
● 3-Ethylpentane	617-78-7	0% TO 5%	S:(2)-9-16-29-33-60-61-62

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed

• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	5 ppm STEL (Cancer hazard, Flammable, See 29 CFR 1910.1028, 15 min); 0.5 ppm Action Level; 1 ppm TWA
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed

• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	(including Benzene from gasoline)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	5000 lb final RQ; 2270 kg final RQ
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	1000 lb final RQ; 454 kg final RQ
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	1000 lb final RQ; 454 kg final RQ
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	10 lb final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule); 4.54 kg final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed

● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	Not Listed
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	Not Listed
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed

- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- Stearic acid 57-11-4 0.1% TO 1% Not Listed
- Naphtha (petroleum), hydrotreated light 64742-49-0 60% TO 100% Not Listed
- Methylcyclohexane 108-87-2 0% TO 20% Not Listed
- 3-Methylhexane 589-34-4 0% TO 30% Not Listed
- Hexane, 2-methyl- 591-76-4 0% TO 15% Not Listed
- Rosin ester 64365-17-9 0.63% Not Listed
- Benzothiazole, 2,2'-dithiobis- 120-78-5 0.1% TO 1% Not Listed
- Propionic acid 79-09-4 < 0.1% Not Listed
- Solvent-refined residual-oils (highly refined) 64742-01-4 0.78% Not Listed
- Carbon Black 1333-86-4 7% TO 13% Not Listed
- Ethylbenzene 100-41-4 < 0.001% 0.1 % de minimis concentration
- Heptane 142-82-5 30% TO 45% Not Listed
- Toluene 108-88-3 < 0.05% 1.0 % de minimis concentration
- Zinc oxide 1314-13-2 0.1% TO 1% Not Listed
- Benzene 71-43-2 < 0.001% 0.1 % de minimis concentration
- White mineral oil 8042-47-5 0.0031% TO 0.0155% Not Listed
- Sulfur 7704-34-9 < 0.1% Not Listed
- Pentane, 2,3-dimethyl- 565-59-3 0% TO 5% Not Listed
- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

- Stearic acid 57-11-4 0.1% TO 1% Not Listed
- Naphtha (petroleum), hydrotreated light 64742-49-0 60% TO 100% Not Listed
- Methylcyclohexane 108-87-2 0% TO 20% Not Listed
- 3-Methylhexane 589-34-4 0% TO 30% Not Listed
- Hexane, 2-methyl- 591-76-4 0% TO 15% Not Listed
- Rosin ester 64365-17-9 0.63% Not Listed
- Benzothiazole, 2,2'-dithiobis- 120-78-5 0.1% TO 1% Not Listed
- Propionic acid 79-09-4 < 0.1% Not Listed
- Solvent-refined residual-oils (highly refined) 64742-01-4 0.78% Not Listed
- Carbon Black 1333-86-4 7% TO 13% Not Listed
- Ethylbenzene 100-41-4 < 0.001% Not Listed
- Heptane 142-82-5 30% TO 45% Not Listed
- Toluene 108-88-3 < 0.05% Not Listed
- Zinc oxide 1314-13-2 0.1% TO 1% Not Listed
- Benzene 71-43-2 < 0.001% Not Listed
- White mineral oil 8042-47-5 0.0031% TO 0.0155% Not Listed
- Sulfur 7704-34-9 < 0.1% Not Listed
- Pentane, 2,3-dimethyl- 565-59-3 0% TO 5% Not Listed
- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII

- Stearic acid 57-11-4 0.1% TO 1% Not Listed

• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Included in waste stream: F039
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	0.057 mg/L (wastewater); 10 mg/kg (nonwastewater)
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	0.080 mg/L (wastewater); 10 mg/kg (nonwastewater)
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	0.14 mg/L (wastewater); 10 mg/kg (nonwastewater)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed

● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	Not Listed
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	
● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed
● Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
● Propionic acid	79-09-4	< 0.1%	Not Listed
● Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
● Carbon Black	1333-86-4	7% TO 13%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	30% TO 45%	Not Listed
● Toluene	108-88-3	< 0.05%	waste number U220
● Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
● Benzene	71-43-2	< 0.001%	waste number U019 (Ignitable waste, Toxic waste)
● White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
● Sulfur	7704-34-9	< 0.1%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

● Stearic acid	57-11-4	0.1% TO 1%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Rosin ester	64365-17-9	0.63%	Not Listed

• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)
• Ethylbenzene	100-41-4	< 0.001%	carcinogen, initial date 6/11/04
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	carcinogen, initial date 2/27/87
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	developmental toxicity, initial date 1/1/91
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	developmental toxicity, initial date 12/26/97
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed

• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	7000 µg/day MADL (level represents absorbed dose)
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	24 µg/day MADL (oral); 49 µg/day MADL (inhalation)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	6.4 µg/day NSRL (oral); 13 µg/day NSRL (inhalation)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	female reproductive toxicity, initial date 8/7/09
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed

- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

- Stearic acid 57-11-4 0.1% TO 1% Not Listed
- Naphtha (petroleum), hydrotreated light 64742-49-0 60% TO 100% Not Listed
- Methylcyclohexane 108-87-2 0% TO 20% Not Listed
- 3-Methylhexane 589-34-4 0% TO 30% Not Listed
- Hexane, 2-methyl- 591-76-4 0% TO 15% Not Listed
- Rosin ester 64365-17-9 0.63% Not Listed
- Benzothiazole, 2,2'-dithiobis- 120-78-5 0.1% TO 1% Not Listed
- Propionic acid 79-09-4 < 0.1% Not Listed
- Solvent-refined residual-oils (highly refined) 64742-01-4 0.78% Not Listed
- Carbon Black 1333-86-4 7% TO 13% Not Listed
- Ethylbenzene 100-41-4 < 0.001% Not Listed
- Heptane 142-82-5 30% TO 45% Not Listed
- Toluene 108-88-3 < 0.05% Not Listed
- Zinc oxide 1314-13-2 0.1% TO 1% Not Listed
- Benzene 71-43-2 < 0.001% male reproductive toxicity, initial date 12/26/97
- White mineral oil 8042-47-5 0.0031% TO 0.0155% Not Listed
- Sulfur 7704-34-9 < 0.1% Not Listed
- Pentane, 2,3-dimethyl- 565-59-3 0% TO 5% Not Listed
- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Stearic acid 57-11-4 0.1% TO 1% Not Listed
- Naphtha (petroleum), hydrotreated light 64742-49-0 60% TO 100% Not Listed
- Methylcyclohexane 108-87-2 0% TO 20% Not Listed
- 3-Methylhexane 589-34-4 0% TO 30% Not Listed
- Hexane, 2-methyl- 591-76-4 0% TO 15% Not Listed
- Rosin ester 64365-17-9 0.63% Not Listed
- Benzothiazole, 2,2'-dithiobis- 120-78-5 0.1% TO 1% Not Listed
- Propionic acid 79-09-4 < 0.1% Not Listed
- Solvent-refined residual-oils (highly refined) 64742-01-4 0.78% Not Listed
- Carbon Black 1333-86-4 7% TO 13% Not Listed
- Ethylbenzene 100-41-4 < 0.001% Not Listed
- Heptane 142-82-5 30% TO 45% Not Listed
- Toluene 108-88-3 < 0.05% Not Listed
- Zinc oxide 1314-13-2 0.1% TO 1% (including fume)
- Benzene 71-43-2 < 0.001% Not Listed
- White mineral oil 8042-47-5 0.0031% TO 0.0155% Not Listed
- Sulfur 7704-34-9 < 0.1% Not Listed
- Pentane, 2,3-dimethyl- 565-59-3 0% TO 5% Not Listed
- 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Not Listed
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	30% TO 45%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.1% TO 1%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

• Stearic acid	57-11-4	0.1% TO 1%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Toxic
• 3-Methylhexane	589-34-4	0% TO 30%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Rosin ester	64365-17-9	0.63%	Not Listed
• Benzothiazole, 2,2'-dithiobis-	120-78-5	0.1% TO 1%	Not Listed
• Propionic acid	79-09-4	< 0.1%	Toxic; Flammable
• Solvent-refined residual-oils (highly refined)	64742-01-4	0.78%	Not Listed
• Carbon Black	1333-86-4	7% TO 13%	Toxic
• Ethylbenzene	100-41-4	< 0.001%	Toxic; Flammable
• Heptane	142-82-5	30% TO 45%	Toxic; Flammable
• Toluene	108-88-3	< 0.05%	Toxic (skin); Flammable (skin)
• Zinc oxide	1314-13-2	0.1% TO 1%	Toxic
• Benzene	71-43-2	< 0.001%	Toxic (skin); Flammable (skin); Carcinogen (skin)
• White mineral oil	8042-47-5	0.0031% TO 0.0155%	Not Listed
• Sulfur	7704-34-9	< 0.1%	Flammable
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 5%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

- Last Revision Date**
- 12/April/2012
- Preparation Date**
- 12/April/2012
- Disclaimer/Statement of Liability**
- The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstance of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

Key to abbreviations

NDA = No data available.
