

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SECTION 1. IDENTIFICATION

Commercial Product Name : Enamel Spray Paint Gloss Black
Product number : 0890000012
SDS-Identcode : 10042967
Product Use Description : Coatings
Company : Würth USA Inc.
93 Grant St.
07446 Ramsey, NJ
USA
Telephone : +1 201 825 27 10
Telefax : +1 201 825 16 43
Responsible/issuing person : prodsafe@wuerth.com
Emergency telephone number : +1 800 255 3924

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight percent- Weight percent
acetone	67-64-1	>= 20 - < 30
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
n-butyl acetate	123-86-4	>= 5 - < 10
4-methylpentan-2-one	108-10-1	>= 5 - < 10
2-(propyloxy)ethanol	2807-30-9	>= 1 - < 5
Barium sulphate	7727-43-7	>= 1 - < 5
isobutyl acetate	110-19-0	>= 1 - < 5
Carbon black	1333-86-4	>= 1 - < 5
pentan-2-one	107-87-9	>= 1 - < 5
cobalt bis(2-ethylhexanoate)	136-52-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : If you feel unwell, seek medical advice (show the label where possible). First aider needs to protect himself. Move out of dangerous area. Never give anything by mouth to an unconscious person. Take off contaminated clothing and shoes immediately.
- Inhalation : If breathed in, move person into fresh air. In the case of inhalation of aerosol/mist consult a physician if necessary. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Skin contact : In case of contact, immediately flush skin with soap and plenty of water. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
- Eye contact : Protect unharmed eye. If easy to do, remove contact lens, if worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ingestion : If swallowed, seek medical advice immediately and show this container or label. If swallowed, DO NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

Notes to physician

Treatment : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

- Form : Aerosol containing a liquefied gas
- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting : Do not use a solid water stream as it may scatter and spread fire.
Hazardous decomposition products may be formed under fire conditions (see section 10).
Exposure to decomposition products may be a hazard to health.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
In the event of fire and/or explosion do not breathe fumes.
Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

- Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.
Remove all sources of ignition.
Avoid contact with skin and eyes.
Ensure adequate ventilation, especially in confined areas.
Immediately evacuate personnel to safe areas.
Avoid inhalation of vapour or mist.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.
Clean contaminated surface thoroughly.

CERCLA Hazardous substances and corresponding RQs:

67-64-1	5,000 lbs <i>final RQ</i>
123-86-4	5,000 lbs <i>final RQ</i>
108-10-1	5,000 lbs <i>final RQ</i>
2807-30-9	<i>final RQ</i>
110-19-0	5,000 lbs <i>final RQ</i>
136-52-7	<i>final RQ</i>

SECTION 7. HANDLING AND STORAGE**Handling**

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

Handling : For personal protection see section 8.
Limit the stocks at work place.
Use only in well-ventilated areas.
Do not breathe vapours or spray mist.
Avoid contact with skin and eyes.
Do not spray on a naked flame or any incandescent material.
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
Take precautionary measures against static discharges.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.
Vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Keep away from heat and sources of ignition.
Do not smoke.
No sparking tools should be used.
Electrical equipment should be protected to the appropriate standard.

Dust explosion class : Not applicable

Storage

Requirements for storage areas and containers : Store in original container.
BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Please observe the storage instructions for aerosols!

Advice on common storage : Incompatible with oxidizing agents.

Other data : No decomposition if stored and applied as directed.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Exposure Guidelines

Components	CAS-No.	List	Type:	Value	Update
acetone	67-64-1	ACGIH	TWA	500 ppm	2013-03-01
		ACGIH	STEL	750 ppm	2013-03-01
		OSHA Z-1	TWA	1,000 ppm 2,400 mg/m ³	1997-08-04
		NIOSH REL	TWA	250 ppm 590 mg/m ³	2013-10-08
		OSHA P0	TWA	750 ppm 1,800 mg/m ³	1989-01-19
		OSHA P0	STEL	1,000 ppm 2,400 mg/m ³	1989-01-19
propane	74-98-6	OSHA Z-1	TWA	1,000 ppm 1,800 mg/m ³	1997-08-04
		NIOSH REL	TWA	1,000 ppm 1,800 mg/m ³	2013-10-08
		OSHA P0	TWA	1,000 ppm 1,800 mg/m ³	1989-01-19
butane	106-97-8	NIOSH REL	TWA	800 ppm 1,900 mg/m ³	2013-10-08
		OSHA P0	TWA	800 ppm 1,900 mg/m ³	1989-01-19
		ACGIH	STEL	1,000 ppm	2014-03-01
n-butyl acetate	123-86-4	ACGIH	TWA	150 ppm	2013-03-01
		ACGIH	STEL	200 ppm	2013-03-01
		OSHA Z-1	TWA	150 ppm 710 mg/m ³	1997-08-04
		NIOSH REL	TWA	150 ppm 710 mg/m ³	2013-10-08
		NIOSH REL	ST	200 ppm 950 mg/m ³	2013-10-08
		OSHA P0	TWA	150 ppm 710 mg/m ³	1989-01-19
4-methylpentan-2-one	108-10-1	OSHA P0	STEL	200 ppm 950 mg/m ³	1989-01-19
		OSHA P0	STEL	200 ppm 950 mg/m ³	1989-01-19
		ACGIH	TWA	20 ppm	2013-03-01
		ACGIH	STEL	75 ppm	2013-03-01
		NIOSH REL	TWA	50 ppm 205 mg/m ³	2013-10-08
		NIOSH REL	ST	75 ppm 300 mg/m ³	2013-10-08
		OSHA Z-1	TWA	100 ppm 410 mg/m ³	1997-08-04
		OSHA P0	TWA	50 ppm 205 mg/m ³	1989-01-19

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

		OSHA P0	STEL	75 ppm 300 mg/m3	1989-01-19
Barium sulphate	7727-43-7	NIOSH REL	TWA	5 mg/m3	2013-10-08
		NIOSH REL	TWA	10 mg/m3	2013-10-08
		OSHA Z-1	TWA	15 mg/m3	2011-07-01
		OSHA Z-1	TWA	5 mg/m3	2011-07-01
		ACGIH	TWA	5 mg/m3	2014-03-01
isobutyl acetate	110-19-0	ACGIH	TWA	150 ppm	2013-03-01
		OSHA Z-1	TWA	150 ppm 700 mg/m3	1997-08-04
		NIOSH REL	TWA	150 ppm 700 mg/m3	2013-10-08
		OSHA P0	TWA	150 ppm 700 mg/m3	1989-01-19
Carbon black	1333-86-4	OSHA Z-1	TWA	3.5 mg/m3	1997-08-04
		NIOSH REL	TWA	3.5 mg/m3	2013-10-08
		NIOSH REL	TWA	0.1 mg/m3	2013-10-08
		OSHA P0	TWA	3.5 mg/m3	1989-01-19
		ACGIH	TWA	3 mg/m3	2013-03-01
pentan-2-one	107-87-9	ACGIH	STEL	150 ppm	2008-01-01
		NIOSH REL	TWA	150 ppm 530 mg/m3	2013-10-08
		OSHA Z-1	TWA	200 ppm 700 mg/m3	1997-08-04
		OSHA P0	TWA	200 ppm 700 mg/m3	1989-01-19
		OSHA P0	STEL	250 ppm 875 mg/m3	1989-01-19
cobalt bis(2-ethylhexanoate)	136-52-7	ACGIH	TWA	0.02 mg/m3	2007-01-01

Engineering measures : Provide sufficient air exchange and/or exhaust in work rooms.

Eye protection : Do not wear contact lenses.
Tightly fitting safety goggles

Hand protection : Wear suitable gloves.
Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Skin and body protection : Flame retardant antistatic protective clothing.
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

- Respiratory protection : Wear respiratory protection.
Product contains low-boiling liquids. Respiratory protective equipment must be air supplied respirators.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
General industrial hygiene practice.
Do not inhale aerosol.
Avoid contact with skin, eyes and clothing.
When using do not eat, drink or smoke.
Wash hands before breaks and at the end of workday.
Follow the skin protection plan.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Aerosol containing a liquefied gas
Physical state : aerosol
- Colour : black
Odour : characteristic
Odour Threshold : No data available
Flash point : No data available
Ignition temperature : No data available
Thermal decomposition : No data available
Lower explosion limit : 1 %(V)
- Upper explosion limit : 13 %(V)
- Flammability : Extremely flammable aerosol.
- Molecular weight : No data available
pH : No data available
- Boiling point/boiling range : No data available
- Vapour pressure : No data available
- Relative vapour density : 4
(Air = 1.0)

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

Evaporation rate	:	No data available
Density	:	0.79 g/cm ³
Relative density	:	No data available
Bulk density	:	No data available
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Solubility in other solvents	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Volatile organic compounds (VOC) content	:	44.83 % 576.29 g/l
PWR limit [g ozone/g product]	:	1.40 (NFP)

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid	:	Heat, flames and sparks.
Materials to avoid	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides
Hazardous reactions	:	Vapours may form explosive mixtures with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Note: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute dermal toxicity	:	Acute toxicity estimate Dose: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Mild respiratory irritant

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

: Acute toxicity estimate
Exposure time: 4 h
Dose: > 40 mg/l
Method: Calculation method

Skin irritation : Prolonged skin contact may cause skin irritation and/or dermatitis.

Carcinogenicity : No data is available on the product itself.
Reproductive toxicity : No data is available on the product itself.
Teratogenicity : No data is available on the product itself.
Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Vapours may cause drowsiness and dizziness.

Component:

acetone

67-64-1

Acute oral toxicity: LD50 Rat
Dose: 5,800 mg/kg

Acute dermal toxicity: LD50 Rabbit
Dose: > 7,426 mg/kg

Acute inhalation toxicity: LC50 Rat
Dose: 76 mg/l/Exposure time: 4 h

Skin irritation: Result: Repeated exposure may cause skin dryness or cracking.

Skin irritation: Guinea pig
Result: No skin irritation

Eye irritation: Rabbit
Result: Irritation to eyes, reversing after 7 to 21 days

Carcinogenicity: Animal testing did not show any carcinogenic effects.

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

butane

106-97-8

Acute inhalation toxicity: LC50 Mouse
Dose: 1,237 mg/l/520400 ppm
Exposure time: 2 h

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

n-butyl acetate	123-86-4	<p><u>Acute oral toxicity</u>: LD50 Rat Dose: > 10,760 mg/kg</p> <p><u>Acute dermal toxicity</u>: LD50 Rabbit Dose: 14,112 mg/kg Method: OECD Test Guideline 402</p> <p><u>Acute inhalation toxicity</u>: LC50 Rat Dose: > 21 mg/l/Exposure time: 4 h Method: OECD Test Guideline 403</p> <p><u>Skin irritation</u>: Result: Repeated exposure may cause skin dryness or cracking.</p>
4-methylpentan-2-one	108-10-1	<p><u>Acute oral toxicity</u>: LD50 Rat Dose: 2,980 mg/kg Method: OECD Test Guideline 401</p> <p><u>Acute dermal toxicity</u>: LD50 Rat Dose: > 2,000 mg/kg Method: OECD Test Guideline 402</p> <p><u>Acute inhalation toxicity</u>: LC50 Rat Dose: > 8.2 - < 16.4 mg/l > 2000 - < 4000 ppm Exposure time: 4 h Method: OECD Test Guideline 403</p> <p><u>Skin irritation</u>: Rabbit Result: No skin irritation Method: OECD Test Guideline 404</p> <p><u>Eye irritation</u>: Rabbit Result: irritating</p> <p><u>Carcinogenicity</u>: Limited evidence of carcinogenicity in animal studies <u>Mutagenicity</u>: In vivo tests did not show mutagenic effects <u>Reproductive toxicity</u>: No toxicity to reproduction</p>
2-(propyloxy)ethanol	2807-30-9	<p><u>Acute dermal toxicity</u>: LD50 Dose: > 1,000 - 2,000 mg/kg</p> <p><u>Eye irritation</u>: Result: Irritating to eyes.</p>
Carbon black	1333-86-4	<p><u>Eye irritation</u>: Result: irritating</p>

Carcinogenicity:**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC

4-methylpentan-2-one	108-10-1
cobalt bis(2-ethylhexanoate)	136-52-7
Carbon black	1333-86-4

SECTION 12. ECOLOGICAL INFORMATIONAdsorbed organic bound : not included
halogens (AOX)Volatile organic : 44.83 %
compounds (VOC)
contentAdditional ecological : The product should not be allowed to enter drains, water
information courses or the soil.**Component:**

acetone

67-64-1

Toxicity to fish:

LC50

Species: Pimephales promelas (fathead minnow)

Dose: 6,210 - 8,120 mg/l

Exposure time: 96 h

Acute and prolonged toxicity for aquatic invertebrates:

EC50

Species: Daphnia pulex (Water flea)

Dose: 8,800 mg/l

Exposure time: 48 h

Toxicity to algae:

NOEC

Species: Microcystis aeruginosa (blue-green algae)

Dose: 530 mg/l

Exposure time: 8 d

Toxicity to bacteria:

Respiration inhibition of activated sludge EC50

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

		Species: Dose: 61.15 mg/l Exposure time: 30 min Method: ISO 8192
n-butyl acetate	123-86-4	<u>Toxicity to fish:</u> LC50 Species: Pimephales promelas (fathead minnow) Dose: 18 mg/l Exposure time: 96 h <u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia (water flea) Dose: 44 mg/l Exposure time: 48 h <u>Toxicity to algae:</u> ErC50 Species: Desmodesmus subspicatus (green algae) Dose: 648 mg/l Exposure time: 72 h
4-methylpentan-2-one	108-10-1	<u>Toxicity to fish:</u> LC50 Species: Brachydanio rerio (zebrafish) Dose: > 179 mg/l Exposure time: 96 h <u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: > 200 mg/l <u>Toxicity to algae:</u> EC50 Species: Lemna gibba (gibbous duckweed) Dose: > 146 mg/l Exposure time: 7 h

SECTION 13. DISPOSAL CONSIDERATIONS

Adequate disposal : In accordance with local and national regulations.
This material and its container must be disposed of as hazardous waste.

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SECTION 14. TRANSPORT INFORMATION**DOT 49 CFR**

ID No : UN 1950
Proper shipping name : Aerosols
Class : 2.1
Labels : 2.1
Emergency Response : 126
Guidebook Number

TDGR

ID No : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Labels : 2.1

ICAO/IATA-DGR

ID No : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
ICAO-Labels : 2.1
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203
Packing instruction (passenger aircraft) : Y203
Environmentally hazardous : no

IMDG-Code

ID No : UN 1950
Description of the goods : AEROSOLS

Class : 2.1
IMDG-Labels : 2.1
EmS Number 1 : F-D
EmS Number 2 : S-U

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
 Fire Hazard
 Sudden Release of Pressure Hazard
 Acute Health Hazard
 Chronic Health Hazard

CERCLA Reportable Quantity : Calculated RQ exceeds reasonably attainable upper limit.

EPCRA_313 US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CAS-No.
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9

EPCRA_302 US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

PENN RTK US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Components	CAS-No.
acetone	67-64-1
Alkyd resin	
propane	74-98-6
butane	106-97-8
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9
Barium sulphate	7727-43-7
isobutyl acetate	110-19-0
Carbon black	1333-86-4
pentan-2-one	107-87-9
xylene	1330-20-7
ethylbenzene	100-41-4
1,2,4-trimethylbenzene	95-63-6

MASS RTK US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

<u>Components</u>	<u>CAS-No.</u>
acetone	67-64-1
propane	74-98-6
butane	106-97-8
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
Barium sulphate	7727-43-7
isobutyl acetate	110-19-0
Carbon black	1333-86-4
pentan-2-one	107-87-9

NJ RTK

US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

<u>Components</u>	<u>CAS-No.</u>
acetone	67-64-1
Alkyd resin	
propane	74-98-6
butane	106-97-8
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9
Barium sulphate	7727-43-7
isobutyl acetate	110-19-0
Carbon black	1333-86-4
pentan-2-one	107-87-9
cobalt bis(2-ethylhexanoate)	136-52-7

California Prop. 65

: WARNING! This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.


Safety Data Sheet

Enamel Spray Paint Gloss Black

Version 5.0

Revision Date 04/06/2015

Print Date 04/08/2015

SECTION 16. OTHER INFORMATION
Further information

HMIS III:

HEALTH	3*
FLAMMABILITY	4
PHYSICAL	2

0 = Insignificant, 1 = Slight,
2 = Moderate, 3 = High, 4 = Extreme

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by : SAP Business Compliance Services GmbH
 Birlenbacher Str. 19
 D-57078 Siegen
 Germany
 Telephone: +49-(0)271-88072-0

Revision Date : 04/06/2015

Date of last issue : 11/24/2014

Date of first issue : 03/20/2012