

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

**SECTION 1. IDENTIFICATION**

Commercial Product Name : Enamel Spray Paint Safety Red  
Product number : 089000013  
SDS-Identcode : 10042741  
Product Use Description : Colouring agent  
Company : Wurth USA Inc.  
93 Grant St.  
07446 Ramsey, NJ  
USA  
Telephone : +1 201 825 27 10  
Telefax : +1 201 825 16 43  
Responsible/issuing person : prodsafe@wuerth.com  
Emergency telephone number : +1 800 255 3924

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Serious eye damage : Category 1  
Carcinogenicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

**GHS Label element**

Hazard pictograms :



Signal word : Danger

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear eye protection/ face protection.  
P280 Wear protective gloves.  
P281 Use personal protective equipment as required.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

container tightly closed.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No.	Weight percent- Weight percent
acetone	67-64-1	>= 20 - < 30
Alkyd Resin		>= 10 - < 20
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
n-butyl acetate	123-86-4	>= 5 - < 10
4-methylpentan-2-one	108-10-1	>= 1 - < 5
2-(propyloxy)ethanol	2807-30-9	>= 1 - < 5
2-methoxy-1-methylethyl acetate	108-65-6	>= 1 - < 5
pentan-2-one	107-87-9	>= 1 - < 5
isobutyl acetate	110-19-0	>= 1 - < 5
cobalt bis(2-ethylhexanoate)	136-52-7	>= 0.1 - < 1
ethylbenzene	100-41-4	>= 0.1 - < 1
distillates (petroleum), hydrotreated light	64742-47-8	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : If you feel unwell, seek medical advice (show the label where possible). First aider needs to protect himself. Move out of dangerous area. Never give anything by mouth to an unconscious person. Take off contaminated clothing and shoes immediately.
- Inhalation : If breathed in, move person into fresh air. In the case of inhalation of aerosol/mist consult a physician if necessary. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Skin contact : In case of contact, immediately flush skin with soap and plenty of water. Do NOT use solvents or thinners. If skin

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

- Eye contact : irritation persists, call a physician.  
: Protect unharmed eye. If easy to do, remove contact lens, if worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ingestion : If swallowed, seek medical advice immediately and show this container or label. If swallowed, DO NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position.

**Notes to physician**

- Treatment : Treat symptomatically and supportively.

**SECTION 5. FIREFIGHTING MEASURES**

- Form : Aerosol containing a liquefied gas  
Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Foam  
Water mist
- Specific hazards during firefighting : Do not use a solid water stream as it may scatter and spread fire.  
Hazardous decomposition products may be formed under fire conditions (see section 10).  
Exposure to decomposition products may be a hazard to health.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
In the event of fire and/or explosion do not breathe fumes.

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately.  
This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water  
must be disposed of in accordance with local  
regulations.  
If the temperature rises there is danger of the vessels  
bursting due to the high vapor pressure.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Refer to protective measures listed in sections 7 and 8.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid contact with skin and eyes.  
Ensure adequate ventilation, especially in confined areas.  
Immediately evacuate personnel to safe areas.  
Avoid inhalation of vapour or mist.  
Beware of vapours accumulating to form explosive  
concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains  
inform respective authorities.
- Methods for cleaning up : Contain and collect spillage with non-combustible  
absorbent material, (e.g. sand, earth, diatomaceous  
earth, vermiculite) and place in container for disposal  
according to local / national regulations.  
Clean contaminated surface thoroughly.

CERCLA Hazardous substances and corresponding RQs:

67-64-1	5,000 lbs <i>final RQ</i>
123-86-4	5,000 lbs <i>final RQ</i>
108-10-1	5,000 lbs <i>final RQ</i>

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

2807-30-9	<i>final RQ</i>
110-19-0	5,000 lbs <i>final RQ</i>
136-52-7	<i>final RQ</i>
100-41-4	1,000 lbs <i>final RQ</i>

**SECTION 7. HANDLING AND STORAGE****Handling**

Handling : For personal protection see section 8.  
Limit the stocks at work place.  
Use only in well-ventilated areas.  
Do not breathe vapours or spray mist.  
Avoid contact with skin and eyes.  
Do not spray on a naked flame or any incandescent material.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
Take precautionary measures against static discharges.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.  
Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Keep away from heat and sources of ignition.  
Do not smoke.  
No sparking tools should be used.  
Electrical equipment should be protected to the appropriate standard.

Dust explosion class : Not applicable

**Storage**

Requirements for storage : Store in original container.

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

areas and containers      BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 Keep containers tightly closed in a dry, cool and well-ventilated place.  
 Please observe the storage instructions for aerosols!

Advice on common storage      : Incompatible with oxidizing agents.  
 Other data      : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Exposure Guidelines**

Components	CAS-No.	List	Type:	Value	Update
acetone	67-64-1	ACGIH	TWA	500 ppm	2013-03-01
		ACGIH	STEL	750 ppm	2013-03-01
		OSHA Z-1	TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	1997-08-04
		NIOSH REL	TWA	250 ppm 590 mg/m <sup>3</sup>	2013-10-08
		OSHA P0	TWA	750 ppm 1,800 mg/m <sup>3</sup>	1989-01-19
		OSHA P0	STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	1989-01-19
propane	74-98-6	OSHA Z-1	TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	1997-08-04
		NIOSH REL	TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	2013-10-08
		OSHA P0	TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	1989-01-19
butane	106-97-8	NIOSH REL	TWA	800 ppm 1,900 mg/m <sup>3</sup>	2013-10-08
		OSHA P0	TWA	800 ppm 1,900 mg/m <sup>3</sup>	1989-01-19
		ACGIH	STEL	1,000 ppm	2013-03-01
n-butyl acetate	123-86-4	ACGIH	TWA	150 ppm	2013-03-01
		ACGIH	STEL	200 ppm	2013-03-01
		OSHA Z-1	TWA	150 ppm 710 mg/m <sup>3</sup>	1997-08-04
		NIOSH REL	TWA	150 ppm 710 mg/m <sup>3</sup>	2013-10-08
		NIOSH REL	ST	200 ppm 950 mg/m <sup>3</sup>	2013-10-08

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

		OSHA P0	TWA	150 ppm 710 mg/m3	1989-01-19
		OSHA P0	STEL	200 ppm 950 mg/m3	1989-01-19
		OSHA P0	STEL	200 ppm 950 mg/m3	1989-01-19
4-methylpentan-2-one	108-10-1	ACGIH	TWA	20 ppm	2013-03-01
		ACGIH	STEL	75 ppm	2013-03-01
		NIOSH REL	TWA	50 ppm 205 mg/m3	2013-10-08
		NIOSH REL	ST	75 ppm 300 mg/m3	2013-10-08
		OSHA Z-1	TWA	100 ppm 410 mg/m3	1997-08-04
		OSHA P0	TWA	50 ppm 205 mg/m3	1989-01-19
		OSHA P0	STEL	75 ppm 300 mg/m3	1989-01-19
2-methoxy-1-methylethyl acetate	108-65-6	US WEEL	TWA	50 ppm	2008-01-01
pentan-2-one	107-87-9	ACGIH	STEL	150 ppm	2008-01-01
		NIOSH REL	TWA	150 ppm 530 mg/m3	2013-10-08
		OSHA Z-1	TWA	200 ppm 700 mg/m3	1997-08-04
		OSHA P0	TWA	200 ppm 700 mg/m3	1989-01-19
		OSHA P0	STEL	250 ppm 875 mg/m3	1989-01-19
isobutyl acetate	110-19-0	ACGIH	TWA	150 ppm	2013-03-01
		OSHA Z-1	TWA	150 ppm 700 mg/m3	1997-08-04
		NIOSH REL	TWA	150 ppm 700 mg/m3	2013-10-08
		OSHA P0	TWA	150 ppm 700 mg/m3	1989-01-19
cobalt bis(2-ethylhexanoate)	136-52-7	ACGIH	TWA	0.02 mg/m3	2007-01-01
ethylbenzene	100-41-4	ACGIH	TWA	20 ppm	2013-03-01
		NIOSH REL	TWA	100 ppm 435 mg/m3	2013-10-08
		NIOSH REL	ST	125 ppm 545 mg/m3	2013-10-08
		OSHA Z-1	TWA	100 ppm 435 mg/m3	1997-08-04
distillates (petroleum), hydrotreated light	64742-47-8	OSHA Z-1	TWA	500 ppm 2,000 mg/m3	2007-01-01
		ACGIH	TWA	200 mg/m3	2010-03-01
		OSHA P0	TWA	400 ppm 1,600 mg/m3	1989-01-19
		OSHA Z-1	TWA	5 mg/m3	2011-07-01
		NIOSH REL	TWA	5 mg/m3	2013-10-08
		NIOSH REL	ST	10 mg/m3	2013-10-08



## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

- Engineering measures : Provide sufficient air exchange and/or exhaust in work rooms.
- Eye protection : Do not wear contact lenses.  
Tightly fitting safety goggles
- Hand protection : Wear suitable gloves.  
Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.  
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.
- Skin and body protection : Flame retardant antistatic protective clothing.  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Wear respiratory protection.  
Product contains low-boiling liquids. Respiratory protective equipment must be air supplied respirators.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
General industrial hygiene practice.  
Do not inhale aerosol.  
Avoid contact with skin, eyes and clothing.  
When using do not eat, drink or smoke.  
Wash hands before breaks and at the end of workday.  
Follow the skin protection plan.  
Wash contaminated clothing before re-use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Aerosol containing a liquefied gas  
Physical state : aerosol
- Colour : red  
Odour : characteristic  
Odour Threshold : No data available  
Flash point : No data available

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Ignition temperature	: No data available
Thermal decomposition	: No data available
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 16 %(V)
Flammability	: Extremely flammable aerosol.
Molecular weight	: No data available
pH	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: No data available
Relative vapour density	: 4.6 (Air = 1.0)
Evaporation rate	: No data available
Density	: 0.78 g/cm <sup>3</sup>
Relative density	: No data available
Bulk density	: No data available
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: Medium: Acetone soluble
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Volatile organic compounds (VOC) content	: 45.82 % 568.72 g/l
PWR limit [g ozone/g product]	1.40 (NFP)

**SECTION 10. STABILITY AND REACTIVITY**

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Strong oxidizing agents

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Hazardous decomposition products : Carbon oxides

Hazardous reactions : Vapours may form explosive mixtures with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Note: No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

Acute dermal toxicity : Acute toxicity estimate  
Dose: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Mild respiratory irritant  
: Acute toxicity estimate  
Exposure time: 4 h  
Dose: > 40 mg/l  
Method: Calculation method

Skin irritation : Prolonged skin contact may cause skin irritation and/or dermatitis.

Eye irritation : Severe eye irritation

Carcinogenicity : No data is available on the product itself.  
Reproductive toxicity : No data is available on the product itself.  
Teratogenicity : No data is available on the product itself.  
Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Vapours may cause drowsiness and dizziness.

**Component:**

acetone

67-64-1

Acute oral toxicity: LD50 Rat  
Dose: 5,800 mg/kg

Acute dermal toxicity: LD50 Rabbit  
Dose: > 7,426 mg/kg

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

		<p><u>Acute inhalation toxicity:</u> LC50 Rat Dose: 76 mg/l/Exposure time: 4 h</p> <p><u>Skin irritation:</u> Result: Repeated exposure may cause skin dryness or cracking.</p> <p><u>Skin irritation:</u> Guinea pig Result: No skin irritation</p> <p><u>Eye irritation:</u> Rabbit Result: Irritation to eyes, reversing after 7 to 21 days</p> <p><u>Carcinogenicity:</u> Animal testing did not show any carcinogenic effects. <u>Mutagenicity:</u> Tests on bacterial or mammalian cell cultures did not show mutagenic effects. <u>Reproductive toxicity:</u> No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.</p>
Alkyd Resin		<p><u>Skin irritation:</u> Result: irritating</p> <p><u>Eye irritation:</u> Result: irritating</p>
butane	106-97-8	<p><u>Acute inhalation toxicity:</u> LC50 Rat Dose: 658 mg/l/Exposure time: 4 h</p>
n-butyl acetate	123-86-4	<p><u>Acute oral toxicity:</u> LD50 Rat Dose: &gt; 10,760 mg/kg</p> <p><u>Acute dermal toxicity:</u> LD50 Rabbit Dose: 14,112 mg/kg Method: OECD Test Guideline 402</p> <p><u>Acute inhalation toxicity:</u> LC50 Rat Dose: &gt; 21 mg/l/Exposure time: 4 h Method: OECD Test Guideline 403</p> <p><u>Skin irritation:</u> Result: Repeated exposure may cause skin dryness or cracking.</p>
4-methylpentan-2-one	108-10-1	<p><u>Acute oral toxicity:</u> LD50 Rat Dose: 2,980 mg/kg Method: OECD Test Guideline 401</p> <p><u>Acute dermal toxicity:</u> LD50 Rat Dose: &gt; 2,000 mg/kg Method: OECD Test Guideline 402</p> <p><u>Acute inhalation toxicity:</u> LC50 Rat Dose: &gt; 8.2 - &lt; 16.4 mg/l &gt; 2000 - &lt; 4000 ppm Exposure time: 4 h</p>

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

		Method: OECD Test Guideline 403
		<u>Skin irritation:</u> Rabbit Result: No skin irritation Method: OECD Test Guideline 404
		<u>Eye irritation:</u> Rabbit Result: irritating
		<u>Carcinogenicity:</u> Limited evidence of carcinogenicity in animal studies
		<u>Mutagenicity:</u> In vivo tests did not show mutagenic effects
		<u>Reproductive toxicity:</u> No toxicity to reproduction
2-(propyloxy)ethanol	2807-30-9	<u>Acute dermal toxicity:</u> LD50 Dose: > 1,000 - 2,000 mg/kg
		<u>Eye irritation:</u> Result: Irritating to eyes.
2-methoxy-1-methylethyl acetate	108-65-6	<u>Acute oral toxicity:</u> LD50 Rat Dose: >= 5,155 mg/kg
		<u>Acute dermal toxicity:</u> LD50 Rat Dose: > 5,000 mg/kg
		<u>Acute inhalation toxicity:</u> LC0 Rat Dose: > 4345 ppm Exposure time: 6 h
		<u>Skin irritation:</u> Rabbit Result: No skin irritation
		<u>Eye irritation:</u> Rabbit Result: No eye irritation
ethylbenzene	100-41-4	<u>Acute inhalation toxicity:</u> LC50 Dose: > 10 - 20 mg/l/Exposure time: 4 h

**Carcinogenicity:**
**ACGIH**

ethylbenzene	100-41-4
4-methylpentan-2-one	108-10-1
distillates (petroleum), hydrotreated light	64742-47-8

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

	cobalt bis(2-ethylhexanoate)	136-52-7
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	
<b>IARC</b>	ethylbenzene	100-41-4
	4-methylpentan-2-one	108-10-1
	cobalt bis(2-ethylhexanoate)	136-52-7

**SECTION 12. ECOLOGICAL INFORMATION**

Adsorbed organic bound halogens (AOX) : not included  
Volatile organic compounds (VOC) content : 45.82 %  
Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

**Component:**

acetone

67-64-1

Toxicity to fish:

LC50

Species: Pimephales promelas (fathead minnow)

Dose: 6,210 - 8,120 mg/l

Exposure time: 96 h

Acute and prolonged toxicity for aquatic invertebrates:

EC50

Species: Daphnia pulex (Water flea)

Dose: 8,800 mg/l

Exposure time: 48 h

Toxicity to algae:

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

		<p>NOEC Species: Microcystis aeruginosa Dose: 530 mg/l Exposure time: 8 d</p> <p><u>Toxicity to bacteria:</u> Respiration inhibition of activated sludge EC50 Species: Dose: 61.15 mg/l Exposure time: 30 min Method: ISO 8192</p>
n-butyl acetate	123-86-4	<p><u>Toxicity to fish:</u> LC50 Species: Pimephales promelas (fathead minnow) Dose: 18 mg/l Exposure time: 96 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia (water flea) Dose: 44 mg/l Exposure time: 48 h</p> <p><u>Toxicity to algae:</u> ErC50 Species: Desmodesmus subspicatus (green algae) Dose: 648 mg/l Exposure time: 72 h</p>
4-methylpentan-2-one	108-10-1	<p><u>Toxicity to fish:</u> LC50 Species: Brachydanio rerio (zebrafish) Dose: &gt; 179 mg/l Exposure time: 96 h</p> <p><u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: &gt; 200 mg/l</p> <p><u>Toxicity to algae:</u> EC50 Species: Lemna gibba Dose: &gt; 146 mg/l Exposure time: 7 h</p>
2-methoxy-1-methylethyl acetate	108-65-6	<p><u>Toxicity to fish:</u> LC50 Species: Oncorhynchus mykiss (rainbow trout) Dose: &gt; 100 - &lt; 180 mg/l Exposure time: 96 h</p>

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Acute and prolonged toxicity for aquatic invertebrates:

EC50

Species: Daphnia magna (Water flea)

Dose: &gt; 500 mg/l

Exposure time: 48 h

Toxicity to algae:

NOEC

Species: Pseudokirchneriella subcapitata (algae)

Dose: &gt;= 1,000 mg/l

Exposure time: 96 h

Toxicity to algae:

ErC50

Species: Pseudokirchneriella subcapitata (algae)

Dose: &gt; 1,000 mg/l

Exposure time: 96 h

Toxicity to bacteria:

Respiration inhibition of activated sludge EC10

Species:

Dose: &gt; 1,000 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

**SECTION 13. DISPOSAL CONSIDERATIONS**

Adequate disposal : In accordance with local and national regulations.  
This material and its container must be disposed of as hazardous waste.

**SECTION 14. TRANSPORT INFORMATION****DOT 49 CFR**

ID No : UN 1950

Proper shipping name : Aerosols

Class : 2.1

Labels : 2.1

Emergency Response : 126

Guidebook Number

**TDGR**

ID No : UN 1950

Proper shipping name : AEROSOLS



## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

Class : 2.1  
Labels : 2.1

**ICAO/IATA-DGR**

ID No : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
ICAO-Labels : 2.1  
Packing instruction (cargo : 203  
aircraft)  
Packing instruction : 203  
(passenger aircraft)  
Packing instruction : Y203  
(passenger aircraft)  
Environmentally hazardous : no

**IMDG-Code**

ID No : UN 1950  
Description of the goods : AEROSOLS  
  
Class : 2.1  
IMDG-Labels : 2.1  
EmS Number 1 : F-D  
EmS Number 2 : S-U  
  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : Sudden Release of Pressure Hazard  
Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

**CERCLA Reportable Quantity** : Calculated RQ exceeds reasonably attainable upper limit.

**EPCRA 302** US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)  
No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

**EPCRA\_313**

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Components</u>	<u>CAS-No.</u>
xylene	1330-20-7
ethylbenzene	100-41-4
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9

**PENN RTK**

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

<u>Components</u>	<u>CAS-No.</u>
acetone	67-64-1
Alkyd Resin	
propane	74-98-6
butane	106-97-8
acrylic copolymer	
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide	2786-76-7
pentan-2-one	107-87-9
isobutyl acetate	110-19-0
xylene	1330-20-7
ethylbenzene	100-41-4

**MASS RTK**

US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

<u>Components</u>	<u>CAS-No.</u>
acetone	67-64-1
propane	74-98-6
butane	106-97-8
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
pentan-2-one	107-87-9
isobutyl acetate	110-19-0

**NJ RTK**

US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0


Revision Date 11/24/2014

Print Date 11/26/2014

Components	CAS-No.
acetone	67-64-1
Alkyd Resin	
propane	74-98-6
butane	106-97-8
acrylic copolymer	
n-butyl acetate	123-86-4
4-methylpentan-2-one	108-10-1
2-(propyloxy)ethanol	2807-30-9
pentan-2-one	107-87-9
isobutyl acetate	110-19-0
cobalt bis(2-ethylhexanoate)	136-52-7
ethylbenzene	100-41-4

**California Prop. 65**

: WARNING! This product contains a chemical known to the State of California to cause cancer.

**SECTION 16. OTHER INFORMATION**
**Further information**

**HMIS III:**

<b>HEALTH</b>	<b>3*</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL</b>	<b>0</b>

 0 = Insignificant, 1 =Slight,  
 2 =Moderate, 3 =High, 4 = Extreme

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## Safety Data Sheet

**Enamel Spray Paint Safety Red**

Version 5.0

Revision Date 11/24/2014

Print Date 11/26/2014

---

Prepared by : SAP Business Compliance Services GmbH  
Birlenbacher Str. 19  
D-57078 Siegen  
Germany  
Telephone: +49-(0)271-88072-0

Revision Date : 11/24/2014

Date of last issue : 03/13/2013

Date of first issue : 02/07/2012

---